

Item no.: 390707

RUTM50 - zellulärer 5G Router

from **480,99 EUR**

Item no.: 390707
shipping weight: 0.50 kg
Manufacturer: Teltonika



 Product Description

RUTM50 is an FCC-certified Teltonika Networks cellular 5G router for North America, with ultra-high cellular speeds of up to 3.4 Gbps. This dual SIM router has auto-failover and backup WAN and supports both SA and NSA 5G architectures. It is also backward compatible with 4G (LTE Cat 19/18), making it perfect for future-proofing your industrial networking solutions. MOBILE- Mobile module: 5G Sub-6 GHz SA, NSA 2.4, 3.4Gbps DL (4x4 MIMO) 900, 550Mbps UL (2x2 MIMO); 4G (LTE): DL Cat 19 1.6Gbps (4x4 MIMO), UL Cat 18 200Mbps- SIM switch: 2 SIM cards, auto-switch cases: weak signal, data limit, SMS limit, roaming, no network, network denied, data connection fail, SIM idle protection- Status: IMSI, ICCID, operator, operator state, data connection state, network type, CA indicator, bandwidth, connected band, signal strength (RSSI), SINR, RSRP, RSRQ, EC/IO, RSCP, data sent/received, LAC, TAC, cell ID, ARFCN, UARFCN, EARFCN, MCC, and MNC- SMS: SMS status, SMS configuration, send/read SMS via HTTP POST/GET, EMAIL to SMS, SMS to EMAIL, SMS to HTTP, SMS to SMS, scheduled SMS, SMS autoreply, SMPP- USSD: Supports sending and reading Unstructured Supplementary Service Data messages- Black/White list: Operator black/white list (by country or separate operators)- Multiple PDN: Possibility to use different PDNs for multiple network access and services- Band management: Band lock, Used band status display- SIM idle protection service: When working with devices with two SIM slots, the one not currently in use will remain idle until the device switches to it, meaning that no data is used on the card until then- APN: Auto APN- Bridge: Direct connection (bridge) between mobile ISP and device on LAN- Passthrough: Router assigns its mobile WAN IP address to another device on LAN- Framed routing: Framed routing: support an IP network behind 5G UEWIRELESS- Wireless mode: 802.11b/g/n/ac Wave 2 (Wi-Fi 5) with data transmission rates up to 867 Mbps (Dual Band, MU-MIMO)- Wi-Fi security: WPA2-Enterprise - PEAP, WPA2-PSK, WPA-EAP, WPA-PSK, WPA3-SAE, WPA3-EAP, OWE; AES-CCMP, TKIP, Auto-cipher modes, client separation, EAP-TLS with PKCS#12 certificates, disable auto-reconnect- SSID/ESSID: ESSID stealth mode- Wi-Fi users: Up to 150 simultaneous connections- Wireless Connectivity Features: Wireless mesh (802.11s), fast roaming (802.11r), Relayd, BSS transition management (802.11v), radio resource measurement (802.11k)- Wireless MAC filter: Whitelist, blacklist- Wireless QR code generator: Once scanned, a user will automatically enter your network without needing to input login information. ETHERNET- WAN: 1 x WAN port 10/100/1000 Mbps, compliance with IEEE 802.3, IEEE 802.3u, 802.3az standards, supports auto MDI/MDIX crossover- LAN: 4 x ETH ports, 10/100/1000 Mbps, supports auto MDI/MDIX crossover- NETWORK- Routing: Static routing, Dynamic routing (BGP, OSPF v2, RIP v1/v2, EIGRP, NHRP), Policy based routing- Network protocols: TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSL v3, TLS, ARP, VRRP, PPP, PPPoE, UPNP, SSH, DHCP, Telnet, SMPP, SNMP, MQTT, Wake On Lan (WOL)- VoIP passthrough support: H.323 and SIP- alg protocol NAT helpers, allowing proper routing of VoIP packets- Connection monitoring: Ping Reboot, Wget Reboot, Periodic Reboot, LCP and ICMP for link inspection- Firewall: Port forward, traffic rules, custom rules- Firewall status page: View all your Firewall statistics, rules, and rule counters- Ports management: View device ports, enable and disable each of them, turn auto-configuration on or off, change their transmission speed, and so on- Network topology: Visual representation of your network, showing which devices are connected to which other devices- Hotspot: Captive portal (hotspot), internal/external Radius server, Radius MAC authentication, SMS authorisation, internal/external landing page, walled garden, user scripts, URL parameters, user groups, individual user or group limitations, user management, 9 default customisable themes and optionally to upload and download customised hotspot themes- DHCP: Static and dynamic IP allocation, DHCP relay, DHCP server configuration, status, static leases: MAC with wildcards- QoS / Smart Queue Management (SQM): Traffic priority queuing by source/destination, service, protocol or port, WMM, 802.11e- DDNS: Supported >25 service providers, others can be configured manually- Network backup: Wi-Fi WAN, Mobile, VRRP, Wired options, each of which can be used as an automatic Failover- Load balancing: Balance Internet traffic over multiple WAN connections- SSHFS: Possibility to mount remote file system via SSH protocol- VRF support: Initial virtual routing and forwarding (VRF) support- SECURITY- Authentication: Pre-shared key, digital certificates, X.509 certificates, TACACS+, Radius, IP & login attempts block, time-based login blocking, built-in random password generator- Firewall: Pre-configured firewall rules can be enabled via WebUI, unlimited firewall configuration via CLI: DMZ: NAT; NAT-T: Attack prevention: DDOS prevention (SYN flood protection, SSH attack prevention, HTTP/HTTPS attack prevention), port scan prevention (SYN-FIN, SYN-RST, X-mas, NULL flags, FIN scan attacks)- VLAN: Port and tag-based VLAN separation- Mobile quota control: Mobile data limit, customizable period, start time, warning limit, phone number- WEB filter: Blacklist for blocking out unwanted websites, Whitelist for specifying allowed sites only- Access control: Flexible access control of SSH, Web interface, CLI and Telnet/VPN - OpenVPN: Multiple clients and a server can run simultaneously, 27 encryption methods- OpenVPN Encryption: DES-CBC 64, RC2-CBC 128, DES-EDE-CBC 128, DES-EDE3-CBC 192, DESX-CBC 192, BF-CBC 128, RC2-40-CBC 40, CAST5-CBC 128, RC2-64-CBC 64, AES-128-CBC 128, AES-128-CFB 128, AES-128-CFB1 128, AES-128-CFB8 128, AES-128-CFB8 192, AES-128-CFB8 256, AES-128-CFB8 192, AES-128-CFB8 256, AES-128-CFB8 192, AES-128-CFB8 256, AES-128-CBC 192, AES-128-GCM 192, AES-128-GCM 256, AES-256-CFB 256, AES-256-CFB1 256, AES-256-CFB8 256, AES-256-CFB8 192, AES-256-CFB8 256, AES-256-CBC 256- IPsec: IKEv1, IKEv2, with 14 encryption methods for IPsec (3DES, DES, AES128, AES192, AES256, AES128GCM, AES192GCM, AES256GCM, AES128GCM12, AES192GCM12, AES256GCM12, AES128GCM16, AES192GCM16, AES256GCM16)- GRE: GRE tunnel, GRE tunnel over IPsec support- PPTP, L2TP: Client/Server instances can run simultaneously, L2TPv3, L2TP over IPsec support- Stunnel: Proxy designed to add TLS encryption functionality to existing clients and servers without any changes in the program's code- DMVPN: Method of building scalable IPsec VPNs- SSTP: SSTP client instance support- ZeroTier: ZeroTier VPN client support- WireGuard: WireGuard VPN client and server support- Tinc: Tinc offers encryption, authentication and compression in it's tunnels. Client and server support- Tailscale: Tailscale offers speed, stability, and simplicity over traditional VPNs. Encrypted point-to-point connections using the open source WireGuard protocol- UA- Supported modes: Client, Server- Supported connection types: TCP/MODBUS- Supported modes: Server, Client- Supported connection types: TCP, USB- Custom registers: MODBUS TCP custom register block requests, which read/write to a file inside the router, and can be used to extend MODBUS TCP Client functionality- Supported data formats: 8-bit: INT, UINT; 16-bit: INT, UINT (MSB or LSB first); 32-bit: float, INT, UINT (ABCD (big-endian), DCBA (little-endian), CDAB, BADC), HEX, ASCII/DATA TO SERVER- Protocol: HTTP(S), MQTT, Azure MQTT- Data to server: Extract parameters from multiple sources and different protocols, and send them all to a single server/MQTT GATEWAY- Modbus MQTT Gateway: Allows sending commands and receiving data from MODBUS Server through MQTT broker/DNP3- Supported modes: Station, Outstation- Supported connection: TCP, USB/DLMS- DLMS Support: DLMS - standard protocol for utility meter data exchange/MONITORING & MANAGEMENT- WEB UI: HTTP/HTTPS, status, configuration, FW update, CLI, troubleshooting, multiple event log servers, firmware update availability notifications, event log, system log, kernel log, Internet status- FOTA: Firmware update from server, automatic notification- SSH: SSH (v1, v2)- SMS: SMS status, SMS configuration, send/read SMS via HTTP POST/GET- Call: Reboot, Status, Mobile data on/off, Output on/off, answer/hang-up with a timer, Wi-Fi on/off- TR-069: OpenACS, EasyCwmp, ACSLite, tGem, LibreACS, GenieACS, FreeACS, LibCWMP, Friendly tech, AVSystem- MQTT: MQTT Broker, MQTT publisher- SNMP: SNMP (v1, v2, v3), SNMP Trap- JSON-RPC: Management API over HTTP/HTTPS- RMS: Teltonika Remote Management System (RMS)IOT PLATFORMS- Cloud of Things: Allows monitoring of: Device data, Mobile data, Network info, Availability- ThingWorx: Allows monitoring of: WAN Type, WAN IP, Mobile Operator Name, Mobile Signal Strength, Mobile Network Type- Cumulocity: Allows monitoring of: Device Model, Revision and Serial Number, Mobile Cell ID, ICCID, IMEI, Connection Type, Operator, Signal Strength, WAN Type and IP- Azure IoT Hub: Can send device IP, Number of bytes send/received, Temperature, PIN count to Azure IoT Hub server, Mobile connection state, Network link state, IMEI, ICCID, Model, Manufacturer, Serial, Revision, IMSI, SIM State, PIN state, GSM signal, WCDMA RSCP, WCDMA EC, IO, LTE RSRP, LTE SINR, LTE RSRQ, CELL ID, Operator, Operator number, Connection type, Temperature, PIN count to Azure IoT Hub server/SYSTEM CHARACTERISTICS- CPU: MediaTek, Dual-Core, 880 MHz, MIPS1004Kc- RAM: 256 MB, DDR3- FLASH storage: 16MB serial NOR flash, 256MB serial NAND flash/FIRMWARE / CONFIGURATION- WEB UI: Update FW from file, check FW on server, configuration profiles, configuration backup- FOTA: Update FW- RMS: Update FW/configuration for multiple devices at once- Keep settings: Update FW without losing current configuration- Factory settings reset: A full factory reset restores all system settings, including the IP address, PIN, and user data to the default manufacturer's configuration/FIRMWARE CUSTOMISATION- Operating system: RutOS (OpenWrt based Linux OS)- Supported languages: Busybox shell, Lua, C, C++, and Python, Java in Package manager- Development tools: SDK package with build environment provided- GPL customization: You can create your own custom, branded firmware and web page application by changing colours, logos, and other elements in our firmware to fit your or your clients' needs/LOCATION TRACKING- GNSS: GPS, GLONASS, BeiDou, Galileo and QZSS- Coordinates: GNSS coordinates via WebUI, SMS, TAVL, RMS- NMEA: NMEA 0183- NTRIP: NTRIP protocol (Networked Transport of RTCM via Internet Protocol)- Server software: Supported server software TAVL, RMS- Geofencing: Configurable multiple geofence zones/USB- Data rate: USB 2.0- Applications: Samba share, USB-to-serial- External devices: Possibility to connect external HDD, flash drive, additional modem, printer, USB-serial adapter- Storage formats: FAT, FAT32, exFAT, NTFS (read-only), ext2, ext3, ext4/INPUT / OUTPUT- Input: 1 x Digital Input, 0 - 6 V detected as logic low, 8 - 50 V detected as logic high- Output: 1 x Digital Output, Open collector output, max output 50 V, 300 mA- Events: Email, RMS, SMS- I/O juggler: Allows to set certain I/O conditions to initiate event/POWER- Connector: 4-pin industrial DC power socket- Input voltage range: 9 - 50 VDC, reverse polarity protection, surge protection >51 VDC 10us max- PoE (passive): Possibility to power up through LAN1 port, not compatible with IEEE802.3af, 802.3at and 802.3bt standards, Mode B, 9 - 50 VDC- Power consumption: Idle: <5 W, Max: <18 W/PHYSICAL INTERFACES- Ethernet: - 5 x RJ45 ports, 10/100/1000 Mbps- I/O's: 1 x Digital Input, 1 x Digital Output on 4-pin power connector- Status LEDs: 3 x connection status LEDs, 3 x connection strength LEDs, 10 x Ethernet port status LEDs, 4 x WAN status LEDs, 1 x Power LED, 2 x 2.4G and 5G Wi-Fi LEDs- SIM: 2 x SIM slots (Mini SIM - 2FF), 1.8 V/3 V- Power: 1 x 4-pin power connector- Antennas: 4 x SMA for Mobile, 2 x RP-SMA for Wi-Fi, 1 x SMA for GNSS- USB: 1 x USB A port for external devices- Reset: Reboot/User default reset/Factory reset button- Other: 1 x Grounding screw/PHYSICAL SPECIFICATION- Casing material: Aluminium housing- Dimensions (W x H x D): 132 x 44.2 x 95.1 mm- Weight: 519 g- Mounting options: DIN rail, wall mount, flat surface (all require additional kit)/OPERATING ENVIRONMENT- Operating temperature: -40 °C to 75 °C- Operating humidity: 10% to 90% non-condensing- Ingress Protection Rating: IP30/REGULATORY & TYPE APPROVALS- Regulatory: FCC, IC, PTCRB, UL/CSA Safety, NOM- Operator: T-Mobile, AT&T (FirstNet)EMC EMISSIONS & IMMUNITY- Standards: 47 CFR Part 15 Subpart B, ICES-003: Issue 7 (October 2020)RF- Standards (Wi-Fi 2.4 GHz, 5 GHz): 47 CFR Part 15 Subpart C - § 15.247, Subpart E - § 15.407/RSS-247 Issue 2 (February 2017), RSS-Gen Issue 5 (April 2018) Amendment 2 (February 2021)KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02KDB 905462 D04 Operational Modes for DFS Testing New Rules v01- Standards (4G, 5G): 47 CFR Part 2, Part 22 Subpart H, Part 24 Subpart E, Part 27 Subpart C, Part 90 Subpart R/S, Part 96, RSS-130 Issue 2 (February 2019), RSS-132 Issue 3 (January 2013), RSS-133 Issue 6 (January 2018) Amendment, RSS-139 Issue 3 (July 2015), RSS-140 Issue 1 (April 2018), RSS-192 Issue 4 (May 2020), RSS-195 Issue 2 (April 2014), RSS-197 Issue 1 (February 2010), RSS-199 Issue 3 (December 2016), RSS-Gen Issue 5 (April 2018) Amendment 2, SRSP-503 Issue 7 (September 2008), SRSP-510 Issue 5 (February 2009), SRSP-513 Issue 3 (July 2015), SRSP-516 Issue 1 (April 2014), SRSP-517 Issue 1 (July 2014), SRSP-518 Issue 2 (February 2019), SRSP-520 Issue 2 (November 2021)RF EXPOSURE- Standards: 47 CFR - § 2.1091, KDB 447498 D04 Interim General RF Exposure Guidance v01, RSS-102 Issue 5 (March 2015) Amendment 1/SAFETY- Standards: UL/CSA Safety: UL 62368-1 (3rd Ed., Rev. December 13, 2019), C22.2 No. 62368-1:19 (3rd Ed., Rev. December 13, 2019)

Specifications

Scan this QR code to view the product
All details, up-to-date prices and availability

