

Item no.: 385554

NPORT 5650-8-DT-J - 8-port RS-232/422/485 desktop device server with RJ45 connectors and 48 VDC power

from **798,79 EUR**

Item no.: 385554
shipping weight: 1.60 kg
Manufacturer: MOXA



Product Description

Our NPort device servers make your serial devices network-ready in an instant. Their compact size makes them ideal for connecting devices such as card readers and payment terminals to an IP-based Ethernet LAN. 8-port RS-232/422/485 desktop device server with RJ45 connectors and 48 VDC power input. Ethernet Interface 10/100BaseT(X) Ports (RJ45 connector) - 2Magnetic Isolation Protection- 1.5 kV (built-in) Ethernet Software Features Configuration Options- Serial Console- Telnet Console- Web Console (HTTP/HTTPS)- Windows Utility/Management- ARP- BOOTP- DHCP Client- DNS- HTTP- HTTPS- ICMP- IPv4- LLDP- Rtelnet- SMTP- SNMPv1/v2c- TCP/IP- Telnet- UDPFilter- IGMP v1/v2 Windows Real COM Drivers- Windows 11/10/8.1/8/7/Vista/XP/ME/98/95- Windows Server 2022/2019/2016/2012 R2/2012/2008 R2/2008/2003- Windows Embedded CE 6.0/5.0, Windows XP Embedded Linux Real TTY Drivers- Kernel versions 6.x, 5.x, 4.x, 3.x, 2.6.x, and 2.4.x Fixed TTY Drivers- macOS Versions: 11.x, 10.12 to 10.15- SCO UNIX, SCO OpenServer, SCO UnixWare 7, Sun Solaris 10, QNX 4.25, QNX 6.x, Solaris 10, FreeBSD, AIX 5.x, HP-UX 11i, Mac OS X Arm®-based Platform Support- Linux Kernel 5.x/4.x Virtual Machine- VMWare ESXi (Windows 11/10)- VMware Fusion (Windows on macOS 10.12 to 11.x)- Parallels Desktop (Windows on macOS 10.12 to 11.x) Android API- Android 3.1.x and later Time Management- SNTPMIB- RFC1213, RFC1317 Security Functions Authentication- Local database Encryption- HTTPS- AES-128- RSA-1024- SHA-1- SHA-256 Security Protocols- HTTPS (TLS 1.2)- SNMPv3 Serial Interface Connector- 8-pin RJ45 No. of Ports- 8 Serial Standards- RS-232/422/485 Baudrate- Supports standard baudrates (unit=bps): 50, 75, 110, 134, 150, 300, 600, 1200, 1800, 2400, 4800, 7200, 9600, 19200, 38400, 57600, 115200, 230.4k, 460.8k, 921.6k Data Bits- 5, 6, 7, 8 Stop Bits- 1, 1.5, 2 Parity- None, Even, Odd, Space, Mark Flow Control- RTS/CTS- DTR/DSR- XON/XOFF Pull High/Low Resistor for RS-485- 1 kilo-ohm, 150 kilo-ohms Terminator for RS-485- 120 ohms RS-485 Data Direction Control- Automatic Data Direction Control (ADDC) Isolation- I models: 2 kV Surge- 0.5 kV Console Port- RS-232 (Tx, Rx, GND), 3-pin (19200, n, 8, 1) Serial Signals RS-232- Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND RS-422- Tx+, Tx-, Rx+, Rx-, GND RS-485- 4w- Tx+, Tx-, Rx+, Rx-, GND RS-485- 2w- Data+, Data-, GND Power Parameters Input Current- 615 mA @ 12 VDC No. of Power Inputs- 2 Input Voltage- 12 to 48 VDC Reverse Polarity Protection- Supported Source of Input Power- TB, Power input jack Reliability Automatic Reboot Trigger- Built-in WDT Alert Tools- Built-in buzzer and RTC (real-time clock) Physical Characteristics Housing- Metal Installation- Desktop- DIN-rail mounting (with optional kit)- Wall mounting (with optional kit) Dimensions (with ears)- 229 x 46 x 125 mm (9.01 x 1.81 x 4.92 in) Dimensions (without ears)- 197 x 44 x 125 mm (7.76 x 1.73 x 4.92 in) Dimensions (with DIN-rail kit on bottom panel)- 197 x 53 x 125 mm (7.76 x 2.09 x 4.92 in) Weight- 1,540 g (3.40 lb) Interactive Interface- LCD panel display- Push buttons for configuration Environmental Limits Operating Temperature- 0 to 55°C (32 to 131°F) Storage Temperature (package included)- -40 to 75°C (-40 to 167°F) Ambient Relative Humidity- 5 to 95% (non-condensing) Standards and Certifications EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 0.5 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m- IEC 61000-4-8 PFMF- IEC 61000-4-11 Safety- UL 60950-1- IEC 62368-1 Declaration Green Product- RoHS, CrRoHS, WEEE MTBF Time- 836,374 hrs Standards- Telcordia (Bellcore) Standard

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

