

Item no.: 387866

## EDS-G205-1GTXSFP-T - Unmanaged full Gigabit Ethernet switch with 4 10/100 1000BaseT(X) ports

from **275,20 EUR**

Item no.: 387866  
shipping weight: 0.90 kg  
Manufacturer: MOXA



### Product Description

Unmanaged Full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 1 Combo 10/100/1000BaseT(X) or 100/1000BaseSFP port, -40 to 75 °C operating temperature  
Input/output interface Alarm contact channels- 1 relay output with a current carrying capacity of 1 A @ 24 VDC Ethernet interface 10/100/1000BaseT(X) ports (RJ45-connection)- 4- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection Combo ports (10/100/1000BaseT(X) or 100/1000BaseSFP+)- 1 Standards- IEEE 802.3 for 10BaseT- IEEE 802.3ab for 1000BaseT(X)- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow control- IEEE 802.3z for 1000BaseX- IEEE 802.3az for energy-efficient Ethernet Switch properties MAC Table Size- 8 K Packet Buffer Size- 1 Mbits Jumbo Frame Size- 10 KB Processing Type- Store and Forward DIPSwitch Configuration Ethernet Interface- Broadcast storm protection- Jumbo Frame- IEEE 802.3az energy saving- 100/1000 SFP speed switching- Port break alarm protection- Supported Input current- 380 mA Physical properties Housing- Metal Protection class- IP30 Dimensions- 29 x 135 x 105 mm (1.14 x 5.31 x 4.13 in) Weight- 290 g (0.64 lb) Installation- DIN rail mounting- Wall mounting (with optional kit) Environmental conditions Operating temperature- -40 to 75 °C (-40 to 167 °F) Storage temperature (including packaging)- - -40 to 85 °C (-40 to 185 °F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications Safety- UL 508- EN 62368-1 (LVD) EMC- EN 55032/35- EN 61000-6-2/-6-4 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMF Hazardous areas- ATEX- Class I Division 2 Railway- EN 50121-4 Vibration- IEC 60068-2-6 Shock- IEC 60068-2-27 Free fall- IEC 60068-2-32 Maritime- ABS- LR- NK- DNVMTB Time- 2,823.446 hours Standards- Telcordia (Bellcore), GB

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

