

Item no.: 387535

TRC-190-AC - Rack housing, 2U, single 110 to 240 VAC input

from **557,09 EUR**

Item no.: 387535
shipping weight: 5.30 kg
Manufacturer: MOXA



Product Description

Moxa's Ethernet-to-fibre media converters feature innovative remote management, industrial-grade reliability and a flexible, modular design that can be adapted to any type of industrial environment. Rack housing, 2U, single 110 to 240 VAC input, with 19 slots on the front. Performance parameters- Input voltage: 100 to 240 VAC- Number of power inputs: 2- Overload current protection: Supported- Current consumption: 1.5 A @ 100 to 240 VAC Physical characteristics- Dimensions: 440 x 260 x 88 mm (17.32 x 10.24 x 3.46 in.)- Installation: 19-inch rack mount- IP rating: IP30- Weight: 5200 g (11.4 lb) Environmental conditions- Ambient relative humidity: 5 to 95% (non-condensing)- Operating temperature: 0 to 60°C (32 to 140°F)- Storage temperature (including packaging): -20 to 75°C (-4 to 167°F) Standards and certifications- EMC: EN 55032/35- EMI: CISPR 32, FCC Part 15B Class A- EMS: IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV(AC), 1 kV(DC) IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m IEC 61000-4-8 PFMF- Environmental testing: IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-3- Safety: IEC 62368-1, UL 62368-1- Vibration: IEC 60068-2-6 MTBF- Time: 1,055,112 hours- Standards: Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

