

Item no.: 387893

SFP-1G10BLC-T - WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km t

from **650,71 EUR**

Item no.: 387893
 shipping weight: 0.10 kg
 Manufacturer: MOXA



Product Description

Moxa's small form-factor pluggable transceiver (SFP) Ethernet fiber modules for Gigabit Ethernet provide coverage across a wide range of communication distances. WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature Ethernet Interface- Ports 1- Connectors Duplex LC connector Simplex LC connector (WDM-type only)- Optical Fiber- Optical Fiber- Optical Fiber- Optical Fiber- Optical Fiber- Optical Fiber Typical Distance: To reach the typical distance of specified fiber transceiver, please refer to formula: Link budget(dB) > dispersion penalty(dB) + total link loss(dB) Power Parameters- Power Consumption Max. 1 W Environmental Limits- Operating Temperature -40 to 85°C (-40 to 185°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- Safety UL 62368-1 IEC 62368-1 IEC 60825-1- EMC EN 55032/35- EMIFCC 15B Test Report ICES-003: 2020 Issue 7- EMS IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV(AC), 0.5 kV(DC); Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 1 kV / 2 kV(AC), 0.5 kV(DC); Signal: 1 kV IEC 61000-4-6 CS: 0.15 MHz to 10 MHz: 3 V, 10 MHz to 30 MHz: 3 to 1 V, 30 MHz to 80 MHz: 1 V IEC 61000-4-8 PFMF: 1 A/m at 50 Hz IEC 61000-4-11 Voltage Dips and Interruption- Maritime DNV

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

