

Item no.: 387484

## IMC-P101-M-ST - PoE industrial 10100BaseT(X) to 100BaseFX media converter, multi-mode port with

from **466,71 EUR**

Item no.: 387484  
shipping weight: 0.70 kg  
Manufacturer: MOXA



### Product Description

PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with ST connector, 0 to 60°C operating temperature Ethernet Interface 100BaseFX Ports (multi-mode ST connector) - 1 Magnetic Isolation Protection - 1.5 kV (built-in) PoE Ports (10/100BaseT(X), RJ45 connector) - 1 Power Parameters Input Current - 360 mA @ 12 to 57 VDC - (HW Rev. 1.1.0 and later) - 430 mA @ 46 to 57 VAC - (HW Rev. 1.0.1 and prior) Input Voltage - 12 to 57 VDC - (HW Rev. 1.1.0 and later) - 46 to 57 VDC - (HW Rev. 1.0.1 and prior) Overload Current Protection - Supported Physical Characteristics Housing - Metal Dimensions - 144.5 x 122.3 x 51.65 mm (5.69 x 4.81 x 2.03 in) Weight - Product only: 532 g (1.17 lb) - Packaged: 701 g (1.55 lb) Installation - DIN-rail mounting Environmental Limits Operating Temperature - 0 to 60°C (32 to 140°F) Storage Temperature (package included) - -40 to 85°C (-40 to 185°F) Ambient Relative Humidity - 5 to 95% (non-condensing) Standards and Certifications EMC - EN 55032/35 EMI - CISPR 32, FCC Part 15B Class A EMS - IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV - IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m - IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV - IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV - IEC 61000-4-6 CS: 150 KHz to 80 MHz: 3 to 1 V - IEC 61000-4-8 PFMF Environmental Testing - IEC 60068-2-2 - IEC 60068-2-3 Safety - UL 508 - EN 62368-1 Vibration - IEC 60068-2-6 MTBF Time - 2,892,595 hrs Standards - Telcordia SR332

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

