

Item no.: 387872

EDS-G308-2SFP - Unmanaged full Gigabit Ethernet switch with 6 10/100 1000BaseT(X) ports

from **366,43 EUR**

Item no.: 387872
shipping weight: 0.90 kg
Manufacturer: MOXA



Product Description

Unmanaged Full Gigabit Ethernet switch with 6 10/100/1000BaseT(X) ports, 2 Combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE series Gigabit/Fast Ethernet modules, 0 to 60 °C operating temperature Input/output interface Alarm contact channels- 1 relay output with a current carrying capacity of 1 A @ 24 VDC Ethernet interface 10/100/1000BaseT(X) ports (RJ45-connection)- 6- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection Combo ports (10/100/1000BaseT(X) or 100/1000BaseSFP+)- 2 standards- IEEE 802.3 for 10BaseT- IEEE 802.3ab for 1000BaseT(X)- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow control- IEEE 802.3z for 1000BaseX- IEEE 802.3az for energy-efficient Ethernet DIP switch configuration Ethernet interface- Broadcast Storm Protection- Jumbo Frame- IEEE 802.3az Energy Saving- 100/1000 SFP Speed Switching- Port Break Alarm Switch Characteristics Jumbo Frame Size- 9.6 KB MAC Table Size- 8 K Packet Buffer Size- 4 Mbits Processing Type- Store and Forward Power Parameters Connection- 1 detachable 6-contact terminal block(s) Input Voltage- 12/24/48 VDC- Redundant dual inputs Operating Voltage- 9.6 to 60 VDC Reverse polarity protection- Supported Input current- 0.9 A @ 12-48 VDC Physical properties Housing- Metall IP protection class- IP30 Dimensions- 52.85 x 135 x 105 mm (2.08 x 5.31 x 4.13 in) Weight- 880 g (1.94 lb) Installation- DIN rail mounting- Wall mounting (with optional kit) Ambient conditions Operating temperature- -10 to 60 °C (14 to 140 °F) Storage temperature (including packaging)- -40 to 85 °C (-40 to 185 °F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications Safety- UL 508- EN 62368-1 (LVD) EMC- EN 55032/35- EN 61000-6-2/-6-4 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 800 MHz; 10 V/m- IEC 61000-4-3 RS: 800 MHz to 1 GHz; 20 V/m- IEC 61000-4-4 EFT; Power: 2 kV; Signal: 2 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMF: 100 A/m Hazardous areas- ATEX- Class I Division 2 Railway- EN 50121-4 Vibration- IEC 60068-2-6 Shock- IEC 60068-2-27 Free fall- IEC 60068-2-32 Maritime- DNV- LR- ABS- NKMTB Time- 2,260.195 hours Standards- Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

