

Item no.: 387874

EDS-G308-T - Unmanaged full Gigabit Ethernet switch with 8 10/100 1000BaseT(X) ports

from **360,56 EUR**

Item no.: 387874
 shipping weight: 0.90 kg
 Manufacturer: MOXA



Product Description

Unmanaged full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, Operating temperature from -40 to 75 °C Input/output interface Alarm contact channels- 1 relay output with a current carrying capacity of 1 A @ 24 VDC Ethernet interface 10/100/1000BaseT(X) ports (RJ45 connector)- 8- Speed with automatic negotiation- Full/half-duplex mode- Auto MDI/MDI-X connection Standards- IEEE 802.3 for 10BaseT- IEEE 802.3ab for 1000BaseT(X)- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow control- IEEE 802.3z for 1000BaseX- IEEE 802.3az for energy-efficient Ethernet DIP switch configuration Ethernet interface- Broadcast storm protection- Jumbo frame- IEEE 802.3az energy saving- 100/1000 SFP speed switching- Port break alarm Switch properties Jumbo frame size- 9.6 KB MAC Table Size- 8 K Packet Buffer Size- 4 Mbits Processing Type- Store and Forward Power Parameters Connection- 1 detachable 6-contact terminal block(s) Input Voltage- 12/24/48 VDC- Redundant dual inputs Operating Voltage- 9.6 to 60 VDC Reverse polarity protection- Supported Input current- 0.8 A @ 12-48 VDC Physical properties Housing- Metall IP protection class- IP30 Dimensions- 52.85 x 135 x 105 mm (2.08 x 5.31 x 4.13 in) Weight- 880 g (1.94 lb) Installation- DIN rail mounting- Wall mounting (with optional kit) Ambient conditions Operating temperature- -40 to 75°C (-40 to 167°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications Safety- UL 508- EN 62368-1 (LVD) EMC- EN 55032/35- EN 61000-6-2/-6-4 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 800 MHz: 10 V/m- IEC 61000-4-3 RS: 800 MHz to 1 GHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMF: 100 A/m Hazardous areas- ATEX- Class I Division 2 Railway- EN 50121-4 Vibration- IEC 60068-2-6 Shock- IEC 60068-2-27 Free fall- IEC 60068-2-32 Maritime- DNV- LR- ABS- NKMTB Time- 2,398.736 hours Standards- Telcordia (Bellcore), GB

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

