

Item no.: 387875

EDS-P206A-4POE-MM-SC - Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multimode ports

from **481,36 EUR**

Item no.: 387875
shipping weight: 0.40 kg
Manufacturer: MOXA



Product Description

Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multimode ports with SC connectors, -10 to 60 °C operating temperature Ethernet interface 100BaseFX ports (multimode SC connectors)- 2PoE ports (10/100BaseT(X), RJ45 connector)- 4- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection Standards- IEEE 802.3 for 10BaseT- IEEE 802.3af/at for PoE/PoE+ output- IEEE 802.3x for flow control- IEEE 802.3u for 100BaseT(X)PoE pinout- V+, V+, V-, V- for pins 1, 2, 3, 6 (Endspan, MDI, Mode A)Switch properties Packet Buffer Size- 768 kbits MAC Table Size- 2 K Processing Type- Store and Forward Power Parameters Input Current- 5.55 A @ 24 VDC Connection- 1 detachable 4-contact terminal block(s) Operating Voltage- 12 to 57 VDC Input Voltage- 12/24/48 VDC- Redundant Dual Inputs Power Budget- Max. 120 W for total PD consumption- Max. 30 W for each PoE port Power Consumption (Max.)- Max. 13.2 W at full load without PD consumption Reverse polarity protection- Supports Overload protection- Supports Physical characteristics Housing- MetallP protection- IP30 Dimensions- 50.3 x 114 x 70 mm (1.98 x 4.53 x 2.76 in) Weight- 375 g (0.83 lb) Installation- DIN rail mounting- wall mounting (with optional kit) Environmental conditions Operating temperature- -10 to 60°C (14 to 140°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMI- CISPR 32, FCC Part 15B Class A EMC- EN 55032/24 EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMFSafety- UL 508 Shock- IEC 60068-2-27 Free fall- IEC 60068-2-31 Vibration- IEC 60068-2-6 MTBF Time- 1.289,258 hours Standards- Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

