

Item no.: 387644

EDS-P206A-4POE-M-SC-T - Unmanaged Ethernet switch with 1 10/100BaseT(X) port, 4 PoE ports

from **462,35 EUR**

Item no.: 387644
shipping weight: 0.40 kg
Manufacturer: MOXA



Product Description

Unmanaged Ethernet switch with 1 10/100BaseT(X) port, 4 PoE ports, 1 100BaseFX multimode port with SC connector, -40 to 75°C operating temperature Ethernet interface 10/100BaseT(X) ports (RJ45 connector)- 1- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection 100BaseFX ports (multi-mode SC connector)- 1PoE ports (10/100BaseT(X), RJ45 connection)- 4- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection Standards- IEEE 802.3 for 10BaseT- IEEE 802.3af/at for PoE/PoE+ output- IEEE 802.3x for flow control- IEEE 802.3u for 100BaseT(X)PoE Pinout- V+, V+, V-, V- for Pins 1, 2, 3, 6 (Endspan, MDI, Mode A)Switch FeaturesPacket Buffer Size- 768 kbitsMAC Table Size- 2 KProcessing Type- Store and ForwardPower ParametersInput Current- 5.55 A @ 24 VDCConnection- 1 detachable 4-contact terminal block(s)Operating Voltage- 12 to 57 VDCInput Voltage- 12/24/48 VDC- Redundant Dual InputsPower Budget- Max. 120 W for total PD consumption- Max. 30 W for each PoE portPower consumption (max.)- Max. 13.2 W at full load without PD consumptionReverse polarity protection- SupportsOverload protection- SupportsPhysical characteristicsHousing- MetallIP protection- IP30Dimensions- 50.3 x 114 x 70 mm (1.98 x 4.53 x 2.76 in)Weight- 375 g (0.83 lb)Installation- DIN rail mounting- Wall mounting (with optional kit)Environmental conditionsOperating temperature- -40 to 75°C (-40 to 167°F)Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F)Relative humidity- 5 to 95% (non-condensing)Standards and certificationsEML- CISPR 32, FCC Part 15B Class AEMC- EN 55032/24EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 1 V- IEC 61000-4-8 PFMFSafety- UL 508Shock- IEC 60068-2-27Free fall- IEC 60068-2-31Vibration- IEC 60068-2-6MTBFTime- 1.289,258 hoursStandards- Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

