

Item no.: 387488

## IMC-P101-S-ST - PoE industrial media converter 10/100BaseT(X) to 100BaseFX

from **651,42 EUR**

Item no.: 387488  
shipping weight: 0.80 kg  
Manufacturer: MOXA



### Product Description

PoE industrial media converter 10/100BaseT(X) to 100BaseFX, single-mode connection with ST connector, operating temperature 0 to 60 °C Ethernet interface 100BaseFX connections (single-mode ST connector)- 1Magnetic insulation protection- 1.5 kV (built-in) PoE ports (10/100BaseT(X), RJ45 connector)- 1Performance parameters Input current- 360 mA @ 12 to 57 VDC- (HW Rev. 1.1.0 and later)- 430 mA @ 46 to 57 VAC- (HW Rev. 1.0.1 and earlier) Input voltage- 12 to 57 VDC- (HW Rev. 1.1.0 and later)- 46 to 57 VDC- (HW Rev. 1.0.1 and earlier) Overload current protection- Supported Physical characteristics Housing- Metal Dimensions- 144.5 x 122.3 x 51.65 mm (5.69 x 4.81 x 2.03 in) Weight- Product only: 532 g (1.17 lb)- Packaged: 701 g (1.55 lb) Installation- DIN rail mounting Environmental conditions Operating temperature- 0 to 60°C (32 to 140°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 150 KHz to 80 MHz: 3 to 1 V- IEC 61000-4-8 PFM Environmental tests- IEC 60068-2-2- IEC 60068-2-3 Safety- UL 508- EN 62368-1 Vibration- IEC 60068-2-6 MTBF Time- 2.892,595 hours Standards- Telcordia SR332

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

