

Item no.: 389393

FPK330 - Connection patch cable in compression technology 330mm

from **12,13 EUR**

Item no.: 389393
shipping weight: 0.10 kg
Manufacturer: Teledesic



Product Description

Patch cable with F compression plugs (Ref. 3802) at the ends. High-quality SK2000plus cable (Ref. 4138xx), triple shielded, Class A++. For connecting e.g. headend components in assembly cabinets. Highlights- Solid copper inner conductor- Triple shielded, Class A++. EU fire protection class EcaFeatures- Colour white, with PVC sheath- Available in various lengthsGood to knowTriple shielded class A++ coaxial cablesDue to the triple shielding, these cables offer the highest level of protection against interference radiation, e.g. caused by LTE/4G signals.Fulfils shielding class A++ according to EN 50117:- At 5 MHz - 30 MHz => TI < 0.9 m²/m- At 30 MHz - 1000 MHz => SA > 105 dB- At 1000 MHz - 2000 MHz => SA > 95 dB- At 2000 MHz - 3000 MHz => SA > 85 dB- The transfer impedance determines how effective the shielding is at low frequencies and the shielding attenuation is defined in the frequency range of 30 MHz-3000 MHz.

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

