

Item no.: 387764

## SFP-2.5GSLC-T - SFP module with 1 2.5GBaseFX port with LC connector, singlemode

from **389,23 EUR**

Item no.: 387764  
shipping weight: 0.10 kg  
Manufacturer: MOXA



### Product Description

The SFP Ethernet fibre optic modules (Small Form Factor Pluggable Transceiver) from Moxa for 2.5 Gigabit Ethernet cover a wide range of communication distances. SFP module with 1 2.5GBaseFX port with LC connector, singlemode, for 5 km transmission, -40 to 85 °C operating temperature. Ethernet interface- Connector: Duplex LC connector- Typical distance: To achieve the typical distance of the specified fibre optic transceiver, please observe the formula:  $\text{Link budget (dB)} > \text{Stray loss (dB)} + \text{Total loss (dB)}$  Performance parameters- Power consumption: Max. 1 W Environmental limits- Operating temperature: -40 to 85°C (-40 to 185°F)- Storage temperature (including packaging): -40 to 85°C (-40 to 185°F)- Ambient relative humidity: 5 to 95% (non-condensing) Standards and certifications- Safety: IEC 60825-1, UL 62368-1, IEC 62368-1- EMC: EN 55032/35- EMI: FCC 15B Test Report, ICES-003: 2020 Issue 7- EMS: IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV(AC), 0.5 kV(DC); Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 1 kV/2 kV(AC), 0.5 kV(DC); Signal: 1 kV IEC 61000-4-6 CS: 0.15 MHz to 10 MHz: 3 V, 10 MHz to 30 MHz: 3 to 1 V, 30 MHz to 80 MHz: 1 V IEC 61000-4-8 PFMF: 1 A/m at 50 Hz IEC 61000-4-11: Voltage dips and interruptions

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

