

Item no.: 387953

UPOINT 1410 - USB to 4-port RS-232 serial hub

from **215,96 EUR**

Item no.: 387953
 shipping weight: 1.40 kg
 Manufacturer: MOXA



Product Description

Moxa's UPort USB-to-serial converters provide computers with high performance, industrial-grade connections for up to 16 serial devices over a single USB port. A wide range of converters are available with features that include SuperSpeed USB 3.2 and Hi-Speed USB 2.0, advanced UARTs for high-end serial performance, COM port mapping, fixed-base COM functionality, and more.

USB to 4-port RS-232 serial hub
 USB InterfaceSpeed- 12 Mbps, 480 Mbps
 USB Connector- USB Type B
 USB Standards- USB 1.1/2.0 compliant
 Serial InterfaceNo. of Ports- 4
 Connector- DB9 male
 Baudrate- 50 bps to 921.6 kbps
 Data Bits- 5, 6, 7, 8
 Stop Bits- 1, 1.5, 2
 Parity- None, Even, Odd, Space, Mark
 Flow Control- None-RTS/CTS- XON/XOFF
 Serial Standards- RS-232 (DB9 male connector)
 Serial SignalsRS-232- Tx+, Tx-, Rx+, Rx-, GND
 RS-485-4w- Tx+, Tx-, Rx+, Rx-, GND
 RS-485-2w- Data+, Data-, GND
 Serial Software FeaturesWindows Drivers- Windows 11/10/8.1/8/7/Vista/XP/ME/98/95- Windows Server 2022/2019/2016/2012 R2/2012/2008 R2/2008/2003/2000/NT
 Linux Drivers- Kernel versions: 6.x, 5.x, 4.x, 3.x, 2.6.x and 2.4.x
 Mac Drivers- macOS versions: 10.12 to 10.15, 11.x
 Virtual Machine- VMware Fusion (Windows on macOS 10.12 to 11.x)- VMWare ESXi (Linux kernel 4)- Parallels Desktop (Windows on macOS 10.12 to 11.x)
 Arm®-based Platform Support- Linux kernel 5.x / 4.x
 Android API- Android 3.1.x and later
 Power ParametersInput Voltage- 12 to 48 VDC
 Input Current- 260 mA @ 12 VDC
 Physical CharacteristicsHousing- Metal
 Dimensions- 204 x 30 x 125 mm (8.03 x 1.18 x 4.92 in)
 Weight- 1,345 g (2.97 lb)
 Environmental LimitsStorage Temperature (package included)- -20 to 75°C (-4 to 167°F)
 Ambient Relative Humidity- 5 to 95% (non-condensing)
 Operating Temperature- 0 to 55°C (32 to 131°F)
 Standards and CertificationsEMC- EN 55032/35
 EMI-CISPR 32, FCC Part 15B Class A
 EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV- IEC 61000-4-5 Surge: Power: 1 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m- IEC 61000-4-8 PFMFSafety- UL 62368-1- IEC 62368-1
 DeclarationGreen Product- RoHS, CRoHS, WEEE
 MTBFTime- 394,441 hrs
 Standards- Telcordia (Bellcore) Standard

Specifications

Scan this QR code to view the product
 All details, up-to-date prices and availability

