

Item no.: 387953

## UPOINT 1410 - USB to 4-port RS-232 serial hub

from **214,08 EUR**

Item no.: 387953  
shipping weight: 1.40 kg  
Manufacturer: MOXA



### Product Description

Moxa's UPort USB-to-serial converters provide computers with high performance, industrial-grade connections for up to 16 serial devices over a single USB port. A wide range of converters are available with features that include SuperSpeed USB 3.2 and Hi-Speed USB 2.0, advanced UARTs for high-end serial performance, COM port mapping, fixed-base COM functionality, and more.

**USB to 4-port RS-232 serial hub**  
**USB Interface** Speed- 12 Mbps, 480 Mbps  
**USB Connector**- USB Type B  
**USB Standards**- USB 1.1/2.0 compliant  
**Serial Interface**No. of Ports- 4  
**Connector**- DB9 male  
**Baudrate**- 50 bps to 921.6 kbps  
**Data Bits**- 5, 6, 7, 8  
**Stop Bits**- 1, 1.5, 2  
**Parity**- None, Even, Odd, Space, Mark  
**Flow Control**- None-RTS/CTS- XON/XOFF  
**Serial Standards**- RS-232 (DB9 male connector)  
**Serial Signals**RS-232- Tx+, Tx-, Rx+, Rx-, GND  
**RS-485-4w**- Tx+, Tx-, Rx+, Rx-, GND  
**RS-485-2w**- Data+, Data-, GND  
**Serial Software Features**Windows Drivers- Windows 11/10/8.1/8/7/Vista/XP/ME/98/95- Windows Server 2022/2019/2016/2012 R2/2012/2008 R2/2008/2003/2000/NT  
**Linux Drivers**- Kernel versions: 6.x, 5.x, 4.x, 3.x, 2.6.x and 2.4.x  
**Mac Drivers**- macOS versions: 10.12 to 10.15, 11.x  
**Virtual Machine**- VMware Fusion (Windows on macOS 10.12 to 11.x)- VMWare ESXi (Linux kernel 4)- Parallels Desktop (Windows on macOS 10.12 to 11.x)  
**Arm@-based Platform Support**- Linux kernel 5.x / 4.x  
**Android API**- Android 3.1.x and later  
**Power Parameters**Input Voltage- 12 to 48 VDC  
**Input Current**- 260 mA @ 12 VDC  
**Physical Characteristics**Housing- Metal  
**Dimensions**- 204 x 30 x 125 mm (8.03 x 1.18 x 4.92 in)  
**Weight**- 1,345 g (2.97 lb)  
**Environmental Limits**Storage Temperature (package included)- -20 to 75°C (-4 to 167°F)  
**Ambient Relative Humidity**- 5 to 95% (non-condensing)  
**Operating Temperature**- 0 to 55°C (32 to 131°F)  
**Standards and Certifications**EMC- EN 55032/35  
**EMI-CISPR 32, FCC Part 15B Class A**EMS- IEC 61000-4-2  
**ESD**: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3  
**RS**: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4  
**EFT**: Power: 1 kV- IEC 61000-4-5  
**Surge**: Power: 1 kV- IEC 61000-4-6  
**CS**: 150 kHz to 80 MHz: 3 V/m- IEC 61000-4-8  
**PFMF**Safety- UL 62368-1- IEC 62368-1  
**Declaration**Green Product- RoHS, CRoHS, WEEE  
**MTBF**Time- 394,441 hrs  
**Standards**- Telcordia (Bellcore) Standard

### Specifications

Scan this QR code to view the product  
All details, up-to-date prices and availability

