

Item no.: 387525

IOPAC 8600-PW10-30W-T - Module for the ioPAC 8600 series, 24-110 VDC, 30 W, two power inputs

from **917,05 EUR**

Item no.: 387525
 shipping weight: 0.40 kg
 Manufacturer: MOXA



Product Description

Module for the ioPAC 8600 series, 24-110 VDC, 30 W, dual power inputs, -40 to 75°C Operating temperature Security functions Authentication- Local database Encryption- AES-256-HMAC- RSA-1024- SHA-1- SHA-256 Security protocols- SNMPv3- SSHv2 Power supply parameters Power connection- Euroblock spring terminal Number of power inputs- 2 Input voltage- 24 to 110 VDC Galvanic isolation- 3k VDC Physical properties Housing- metal Weight- 370 g (0.82 lb) Wiring- Power cord, 14 to 28 AWG Ambient conditions Operating temperature- -40 to 75°C (-40 to 167°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Altitude- 2000 m Standards and certifications EMC- EN 55032/35- EN 61000-6-2/-6-4 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 5100 MHz to 6000 MHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMF Railway- EN 50121-4- EN 50155 Safety- UL 508 Shock- IEC 60068-2-27 Vibration- IEC 60068-2-6 MTBF Time- ioPAC 8600-CPU30 models (HW Rev 1.0.1): 1,358,656 hours- ioPAC 8600-CPU30 models (HW Rev. 1.1.0): 1,273,872 hours- ioPAC 8600-PW10-15W-T: 1,752,960 hours- ioPAC 8600-PW10-30W-T: 1,341,777 hours- ioPAC 8600-BM005-T: 2,678,587 hours- ioPAC 8600-BM009-T: 1,350,621 hours- ioPAC 8600-BM012-T: 1,238,479 hours Standards- Telcordia SR332

Specifications

Scan this QR code to view the product
 All details, up-to-date prices and availability

