

Item no.: 387525

## IOPAC 8600-PW10-30W-T - Module for the ioPAC 8600 series, 24-110 VDC, 30 W, two power inputs

from **971,20 EUR**

Item no.: 387525  
 shipping weight: 0.40 kg  
 Manufacturer: MOXA



### Product Description

Module for the ioPAC 8600 series, 24-110 VDC, 30 W, dual power inputs, -40 to 75°C Operating temperature  
 Security functions  
 Authentication- Local database  
 Encryption- AES-256-HMAC- RSA-1024- SHA-1- SHA-256  
 Security protocols- SNMPv3- SSHv2  
 Power supply parameters  
 Power connection- Euroblock spring terminal  
 Number of power inputs- 2  
 Input voltage- 24 to 110 VDC  
 Galvanic isolation- 3k VDC  
 Physical properties  
 Housing- metal  
 Weight- 370 g (0.82 lb)  
 Wiring- Power cord, 14 to 28 AWG  
 Ambient conditions  
 Operating temperature- -40 to 75°C (-40 to 167°F)  
 Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F)  
 Relative humidity- 5 to 95% (non-condensing)  
 Altitude- 2000 m  
 Standards and certifications  
 EMC- EN 55032/35- EN 61000-6-2/-6-4  
 EMI- CISPR 32, FCC Part 15B Class A  
 EMS- IEC 61000-4-2  
 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3  
 RS: 5100 MHz to 6000 MHz: 3 V/m- IEC 61000-4-4  
 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5  
 Surge: Power: 2 kV; Signal: 1 kV- IEC 61000-4-6  
 CS: 10 V- IEC 61000-4-8  
 PFMFRailway- EN 50121-4- EN 50155  
 Safety- UL 508  
 Shock- IEC 60068-2-27  
 Vibration- IEC 60068-2-6  
 MTBF  
 Time- ioPAC 8600-CPU30 models (HW Rev 1.0.1): 1,358,656 hours- ioPAC 8600-CPU30 models (HW Rev. 1.1.0): 1,273,872 hours- ioPAC 8600-PW10-15W-T: 1,752,960 hours- ioPAC 8600-PW10-30W-T: 1,341,777 hours- ioPAC 8600-BM005-T: 2,678,587 hours- ioPAC 8600-BM009-T: 1,350,621 hours- ioPAC 8600-BM012-T: 1,238,479 hours  
 Standards- Telcordia SR332

### Specifications

Scan this QR code to view the product  
 All details, up-to-date prices and availability

