

Item no.: 389394

FPK390 - Connection patch cable in compression technology 390mm

from **12,22 EUR**

Item no.: 389394
shipping weight: 0.10 kg
Manufacturer: Teledesic



Product Description

Patch cable with F compression plugs (Ref. 3802) at the ends. High-quality SK2000plus cable (Ref. 4138xx), triple shielded, Class A++. For connecting e.g. headend components in assembly cabinets. Highlights - Solid copper inner conductor - Triple shielded, Class A++. EU fire protection class Eca. Features - Colour white, with PVC sheath - Available in various lengths. Good to know - Triple shielded class A++ coaxial cables. Due to the triple shielding, these cables offer the highest level of protection against interference radiation, e.g. caused by LTE/4G signals. Fulfills shielding class A++ according to EN 50117: - At 5 MHz - 30 MHz => TI < 0.9 m²/m - At 30 MHz - 1000 MHz => SA > 105 dB - At 1000 MHz - 2000 MHz => SA > 95 dB - At 2000 MHz - 3000 MHz => SA > 85 dB - The transfer impedance determines how effective the shielding is at low frequencies and the shielding attenuation is defined in the frequency range of 30 MHz-3000 MHz.

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

