

Item no.: 386182

## ONCELL G4302-LTE4-EU - Industrial LTE Cat. 4 cellular secure router, B1B3B7B8B20B28

from 1.032,28 EUR

Item no.: 386182  
shipping weight: 0.70 kg  
Manufacturer: MOXA



### Product Description

Industrial applications with mobile communication - such as moving vehicles, industrial M2M and the monitoring of geographically dispersed locations - must be reliable and fail-safe even in dynamic and radio-hostile environments. Our industrial-grade cellular routers are able to meet this challenge and enable reliable mobile data access anytime, anywhere.

**Industrial LTE Cat. 4 Cellular Secure Router, B1/B3/B7/B8/B20/B28, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature**

Cellular Interface Cellular Standards- LTE CAT 4, HSPA, UMTS, EDGE, GPRS, GSM LTE Data Rate- 20 MHz bandwidth: 150 Mbps DL, 50 Mbps UL Band options (EU)- LTE B1 (2100 MHz) / B3 (1800 MHz) / B7 (2600 MHz) / B8 (900 MHz) / B20 (800 MHz) / B28 (700 MHz)- UMTS/HSPA B1 (2100 MHz) / B8 (900 MHz)- GSM/GPRS/EDGE 900 MHz / 1800 MHz Number of SIM cards- 2 slots SIM format- Nano-SIM Connections for mobile phone antennas- 2 SMA sockets Ethernet interface 10/100/1000BaseT(X) ports (RJ45 connection)- 2 GNSS interface GNSS bands- GPS (1575.42 MHz)- GLONASS (1597.52 MHz)- Galileo (1575.42 MHz)- BeiDou (1561.098 MHz) GNSS antenna connectors- 1 SMA socket Input/output interface Digital output channels- 1- Relay output with a current carrying capacity of 1 A @ 24 VDC Digital input channels- 1 Digital inputs- -30 to +3 V for state 0- +13 to +30 V for state 1 Buttons- Reset button USB interface No. of USB ports - 1 of USB ports- 1 USB port- USB type A USB standards- USB 2.0 Serial interface Number of ports- 1 Connector- DB9 male Serial standards- RS-232/422/485 Data bits- 5, 6, 7, 8 Stop bits- 1, 1.5, 2 Parity- None- Even- Odd Baud rate- 300 bps to 921.6 kbps Console connection- RS-232 (Tx, Rx, GND), USB Type-C (115200, n, 8, 1) Serial signals RS-232- Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND RS-422- Tx+, Tx-, Rx+, Rx-, GND RS-485- 2w- Data+, Data-, GND RS-485- 4w- Tx+, Tx-, Rx+, Rx-, GND Operating modes Standards- Real COM mode- RFC2217 mode- TCP client mode- TCP server mode- UDP mode LED interface LED indicators- PWR1, PWR2, STATE, USB, SIM1, SIM2, CELL, LTE, GNSS, SERIAL, VPN Ethernet software functions- GuardLink- Power Management- Back Pressure Flow Control- LLDP- Syslog- Wireless Search Utility- MXview One- MXconfig- MXsecurity- Moxa Remote Connect (MRC) Broadcast Forwarding- IP directed broadcast, Broadcast forwarding Configuration options- Serial console (HTTP/HTTPS)- Command line interface (CLI) via serial/Telnet/SSH Network protocols- DDNS - DHCP DDNS- DHCP server/client- SMTP- SNMPv1/v2c/v3- ARP- Telnet- TCP/IP- UDP- SMS remote control Filter- 802.1Q VLAN- Port-based VLAN Unicast routing- Static route Multicast routing- Static route Routing redundancy- VRRP Time management- NTP Server/Client- SNTP Security functions Hardware-based security- Secure Boot Password- Password protection at user level Authentication- Local database - RADIUS Local database- RADIUS Access control list Firewall Filter- DDoS- Ethernet protocols- ICMP- IP address- MAC address- Ports NAT Functions Ports NAT Functions- 1-to-1- N-to-1- PAT- NAT loopback- Double NAT IPsec VPN Authentication- MD5 and SHA (SHA-256)- RSA (key size: 1024-bit, 2048-bit)- Pre-shared key or X.509 v3 certificate Encryption- DES- 3DES- AES-128- AES-192- AES-256 Simultaneous VPN tunnels- Max. 15 IPsec VPN tunnels Protocols- IPsec Performance parameters Input current- 0.96 A @ 12 VDC (max.)- 0.63 A @ 12 VDC (average)- 0.33 A @ 24 VDC (average)- 0.18 A @ 48 VDC (average) Input voltage- 12 to 48 VDC Power consumption- 7.6 W (typ.)- 11.52 W (max.) Mains connection- Screw terminal block Reverse polarity protection- Supported Physical characteristics Housing- Metal Dimensions- 125 x 46.2 x 100 mm (4.92 x 1.82 x 3.94 in) Weight- 610 g (1.34 lb) Installation- DIN rail mounting- Wall mounting (with optional kit) IP rating- IP40 Environmental conditions Operating temperature- -10 to 55°C (14 to 131°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMC- EN 55032/35- EN 61000-6-2/-6-4 EMI- CISPR 22, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz; 10 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV- IEC 61000-4-5 Surge: Power: 2 kV, Signal: 2 kV- IEC 61000-4-6 CS: 10 V; 150 kHz to 80 MHz- IEC 61000-4-8: 30 A/m Free fall- IEC 60068-2-32 Hazardous areas- IECEx - ATEX - Class I Division 2 Railway- EN 50121-4 Traffic control- NEMA TS2 Road vehicles- E-mark E1 Radio Frequency- FCC- PTCRB- EN 303 413 Radio- NCC- TELEC- RCM- KC- ICID- UKCA- Anatel Network Operator Authorisations- Verizon- AT&T Mobile radio standards- EN 301 489-1/-19- EN 301 489-1/-52- EN 301511- EN 301908-1/-2/-13 Safety- UL 62368-1- EN 62368-1 Shock- IEC 60068-2-27 Vibration- IEC 60068-2-6 MTBF Time- 518,722 hours Standards- Telcordia SR332

### Specifications

Scan this QR code to view the product  
All details, up-to-date prices and availability

