

Item no.: 385694

MIINEPORT E3-H - Embedded device server for TTL devices, pin header module, 10100M with RJ45 connection

from **72,69 EUR**

Item no.: 385694
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connection, 50 bps to 921.6 Kbps baud rate, 0 to 55°C Operating temperature Embedded System CPU- 32-bit Arm Core Memory Flash- 2 MB SDRAM- 4 MB Input/Output Interface Configurable DIO channels (via software)- 4 Ethernet Interface Magnetic isolation protection- 1.5 kV (built-in) PoE Pass-through- IEEE 802.3af for PoE 10/100 Base T(X) ports, Auto MDI/MDI-X- 8-pin RJ45 Ethernet software features Configuration options- Web Console (HTTP), Windows Utility Management- ARP, BOOTP, Device Search Utility (DSU), DHCP Client, IPv4, SMTP, SNMPv1, TCP/IP, Telnet, TFTP, UDP, ICMP Windows Real COM driver- Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows 2008 R2/2012/2012 R2 (x64), Windows Embedded CE 5.0/6.0, Windows XP Embedded Linux Real TTY driver- Kernel versions: 2.4.x, 2.6.x, 3.x, 4.x, and 5.x Fixed TTY Drivers- SCO UNIX, SCO OpenServer, UnixWare 7, QNX 4.25, QNX 6, Solaris 10, FreeBSD, AIX 5.x, HP-UX 11i, Mac OS X Android API- Android 3.1.x and higher Serial interface Number of ports- 1 Serial standards- TTL Operating modes- Real COM mode, TCP server mode, TCP client mode, UDP mode, RFC2217 mode, Ethernet modem mode Baud rate- 50 bps to 921.6 kbps Data bits- 5, 6, 7, 8 Stop bits- 1, 1.5, 2 Parity- None, Even, Odd, Space, Mark Flow control- None, RTS/CTS, DTR/DSR, XON/XOFF Serial signals TTL- Tx, Rx, RTS, CTS, DTR, DSR, DCD, RST (reset circuit), GND NetEZ technology NetEZ functions- EZPower, EZPage, SCM (serial command mode), AutoCFG Power parameters Input current- 157 mA @ 3.3 VDC Input voltage- 3.3 to 5 VDC Physical characteristics Dimensions- 35 x 52.5 x 18 mm (1.38 x 2.07 x 0.71 in) Weight- 12 g (0.03 lb) Environmental conditions Operating temperature- 0 to 55°C (32 to 131°F) Storage temperature (in packaging)- -40 to 60°C (-40 to 140°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMC- EN 55032/24 EMI- CISPR 32, FCC Part 15B Class B EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 2 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m- IEC 61000-4-8 PFMF- IEC 61000-4-11 DIPs Environmental tests- IEC 60068-2-1- IEC 60068-2-3 Shock- IEC 60068-2-27 Vibration- IEC 60068-2-6 Free fall- IEC 60068-2-6 Declaration Green Product- RoHS, CRoHS, WEEE MTBF Time- 5,696,350 hours Standards- Telcordia SR332

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

