

Item no.: 384681

OBU-102-SS-SC - 2-channel fibre optic bypass unit with 4 singlemode ports, SC

from **1.128,19 EUR**

Item no.: 384681
shipping weight: 0.80 kg
Manufacturer: MOXA



Product Description

2-channel fibre optic bypass unit with 4 single-mode ports, SC, -20 to 70°C operating temperature Ethernet interface- Single-mode fibre, SC socket: 4 Bypass properties- Optical switching time: 10 ms (max.)- Insertion loss: 1.6 dB (max.) Rotary switch configuration - Boot delay interval: 10 steps, each step corresponds to a 5-second delay Performance parameters - Input voltage: 1.6 dB (max.) Rotary switch configuration- Boot delay interval: 10 steps, each step corresponds to a 5-second delay Power parameters- Input voltage: 12/24/48 VDC, redundant dual inputs- Input current: 0.1 A @ 48 VDC- Reverse polarity protection: Supported Physical properties- Housing: Metal- IP protection class: IP30- Dimensions: 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)- Weight: 700 g (1.54 lb)- Installation: DIN rail mounting, wall mounting (with optional kit) Environmental conditions- Operating temperature: -20 to 70°C (-4 to 158°F)- Storage temperature (including packaging): -40 to 85°C (-40 to 185°F)- Ambient relative humidity: 5 to 95% (non-condensing) Standards and certifications- Safety: UL 508- EMC: EN 55032/24- EMI: CISPR 32, FCC Part 15B Class A- EMS: IEC 61000-4-2 ESD: Contact: 6 kV; air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV IEC 61000-4-5 Surge: Power: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Free fall: IEC 60068-2-31- Shock: IEC 60068-2-27- Vibration: IEC 60068-2-6

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

