

Item no.: 385891

VPOR P06-1MP-M12-CAM28 - EN 50155, HD image, compact IP camera, M12 connection, 1 audio input

from **581,47 EUR**

Item no.: 385891
shipping weight: 0.40 kg
Manufacturer: MOXA



Product Description

Our range of IP cameras includes dome and box cameras as well as cameras with a robust design. They fulfil parts of the EN 50155 standard and therefore offer reliable performance and excellent image quality for a range of applications. EN 50155, HD image, compact IP camera, M12 connection, 1 audio input, PoE, 2.8 mm lens, -25 to 55°C operating temperature, Ethernet interface, PoE connections (10/100BaseT(X), M12 D-coded 4-pin socket), 1 Ethernet software features, Protocols- TCP/IP- IPv4- UDP- HTTP- RTP/RTSP- ARP- UPnP- FTP- TFTP- NTP client- DNS- QoS- IGMP v3- ICMP- SNMPv1/v2c/v3- DHCP Opt66/67- HTTPS, Security functions, Password- Password protection at user level, Filter- IP address, Encryption- HTTPS, Performance parameters, Number of power inputs- 1, Power source- PoE (IEEE 802.3af), Input current- 0.12 A @ 48 VDC, Camera features, Sensor- 1/2.7-in HD progressive scan CMOS, Lens- f=2.8 mm, F2.0, Diagonal 126°, Horizontal 113°, Vertical 58°, Camera angle- Pan: ±30°, Tilt: 0° to 90° (manually controlled), Minimum illumination- Colour: 0.2 Lux, at F1.2 (Gain High, 50 IRE, 1/30 sec.), Synchronisation- Internal, White balance- ATW/AWB, Electronic shutter- Automatic, fixed (1/30 to 1/25000 sec.), Signal-to-noise ratio- Maximum 50 dB (AGC off; DNR on), DNR (digital noise reduction)- Integrated 2D/3D DNR, WDR (Wide Dynamic Range)- 110 dB, Flickerless Control- Automatic, 50 Hz, 60 Hz modes, Image rotation- Flip, mirror, and 180° rotation, Image adjustment- Manual adjustment with saturation, Sharpness and contrast, AGC (automatic gain control)- 2x, 4x, 8x, 16x, 32x, 64x, BLC (backlight compensation)- High/Medium/Low, Video interface, Video compression- H.264 (ISO/IEC 14496-10) or MJPEG, Video output- via Ethernet, Video streams- 3 independent H.264 or MJPEG video streams, Video resolution and FPS (frames per second) Video viewing- DynaStream™ support for automatically changing the video frame rate- CBR Pro™ for good image quality for transmissions with limited bandwidth- 3 areas for data protection masks- Adjustable image size and quality- Timestamp and text overlay- OSD (On Screen Display) position adjustable- Maximum 5 simultaneous unicast connections, 50 multicast clients, Audio interface, Audio inputs- 1 x line-in, with RCA connection, Audio format- Mono, PCM (G.711), Camera software development, Video standards- ONVIF profile S, Camera alarm software functions, Intelligent video- Camera tampering detection, Video motion detection- 3 independently configurable areas, Scheduling- Daily recurring schedule, Imaging- JPEG snapshots for pre/trigger/post-alarm images/Post-alarm images, Customised alarms- HTTP event server for setting customised alarm actions, FTP messaging- Automatic transfer of stored images via FTP as event-driven actions, Software requirements, Memory size- 1 GB, Operating system- Windows 7 or higher, Browser- Internet Explorer 9.x or higher, Multimedia- DirectX 9.0C or higher, Physical properties, Housing- Plastic top cover, metal base plate- IP66 protection against rain and dust- IK10 protection against vandalism- Transparent PC cover, Dimensions- 110 x 47 mm (4.33 x 1.85 in), Weight- 310 g (0.68 lb), Installation- Panel mounting, Ambient conditions, Operating temperature- -25 to 55°C (-13 to 131°F), Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F), Relative humidity- 5 to 95% (non-condensing), Protection class- IEC 60529, IP66, Vandalism resistance- EN 62262, IK10, Altitude- 2000 m, Standards and certifications, EMI- CISPR 32, FCC Part 15B Class A, EMS- IEC 61000-4-2 ESD: Contact: 6 kV; air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m- IEC 61000-4-4 EFT: Signal: 2 kV- IEC 61000-4-5 Surge: Signal: 1 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFM, Free fall- IEC 60068-2-31, Railway fire protection- EN 45545-2, Safety- UL 62368-1, Shock- IEC 60068-2-27, IEC 61373, EN 50155, Vibration- IEC 60068-2-64, IEC 61373, EN 50155, Railway- EN 50155 (fulfils part of the EN 50155 specifications), MTBF, Time- 1.944,687 hours, Standards- Telcordia SR332

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

