

Item no.: 387752

SFP-1GLHXLC-T - SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40

from **748,23 EUR**

Item no.: 387752
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Moxa's small form-factor pluggable transceiver (SFP) Ethernet fiber modules for Gigabit Ethernet provide coverage across a wide range of communication distances. SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature Ethernet Interface Ports: 1 Connectors- Duplex LC connector- Simplex LC connector (WDM-type only) Optical Fiber- Typical Distance: To reach the typical distance of specified fiber transceiver, please refer to formula: Link budget(dB) > dispersion penalty(dB) + total link loss(dB) Power Parameters Power Consumption- Max. 1 W Environmental Limits Operating Temperature- -40 to 85°C (-40 to 185°F) Storage Temperature (package included)- -40 to 85°C (-40 to 185°F) Ambient Relative Humidity- 5 to 95% (non-condensing) Standards and Certifications Safety- UL 62368-1- IEC 62368-1- IEC 60825-1 EMC- EN 55032/35 EMI- FCC 15B Test Report- ICES-003: 2020 Issue 7 EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV(AC), 0.5 kV(DC); Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 1 kV / 2 kV(AC), 0.5 kV(DC); Signal: 1 kV- IEC 61000-4-6 CS: 0.15 MHz to 10 MHz: 3 V, 10 MHz to 30 MHz: 3 to 1 V, 30 MHz to 80 MHz: 1V- IEC 61000-4-8 PFMF: 1 A/m at 50 Hz- IEC 61000-4-11 Voltage Dips and Interruption Maritime- DNV

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

