

Item no.: 387758

SFP-1GSXLC-T - SFP module with 1 1000BaseSX port with LC connection for 300m550m transmission

from **186,34 EUR**

Item no.: 387758
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Moxa's Small Form-Factor Pluggable Transceiver (SFP) Ethernet fibre optic modules for Gigabit Ethernet cover a wide range of communication distances. SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, -40 to 85°C operating temperature Ethernet interface Ports- 1 Connectors- Duplex LC connector- Simplex LC connector (WDM type only) Fibre optic- Typical distance: To achieve the typical distance of the specified fibre optic transceiver, please refer to the formula: Link budget(dB) > Scattering loss(dB) + Total loss(dB) Performance parameters Power consumption- Max. 1 W Ambient conditions Operating temperature- -40 to 85°C (-40 to 185°F) Storage temperature (in packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications Safety- UL 62368-1- IEC 62368-1 IEC 60825-1 EMC- EN 55032/35 EMI- FCC 15B Test Report- ICES-003: 2020 Edition 7 EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV(AC), 0.5 kV(DC); Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 1 kV / 2 kV(AC), 0.5 kV(DC); Signal: 1 kV- IEC 61000-4-6 CS: 0.15 MHz to 10 MHz: 3 V, 10 MHz to 30 MHz: 3 to 1 V, 30 MHz to 80 MHz: 1 V- IEC 61000-4-8 PFMF: 1 A/m at 50 Hz- IEC 61000-4-11 Voltage dips and interruptions Maritim- DNV

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

