

Item no.: 386190

PTC-101-M-LC-HV - Industrial 10/100BaseT(X) to 100BaseFX media converter, multimode

from **483,54 EUR**

Item no.: 386190
shipping weight: 1.00 kg
Manufacturer: MOXA



Product Description

Industrial 10/100BaseT(X) to 100BaseFX media converter, multimode with LC connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C Operating temperature Ethernet interface 10/100BaseT(X) ports (RJ45 connector)- 1 100BaseFX ports (multimode LC connector)- 1 Magnetic isolation protection- 1.5 kV (built-in) Performance parameters Input voltage- 100 to 240 VAC, 100 to 240 VAC, 100 to 240 VDC Input current- 350 to 200 mA @ 100 to 240 VAC- 350 to 200 mA @ 100 to 240 VDC Overload current protection- Supported Current consumption- 350 to 200 mA @ 100 to 240 VAC- 350 to 200 mA @ 100 to 240 VDC Physical characteristics Housing- Metal Dimensions- 152.15 x 126.46 x 66.65 mm (5.99 x 4.86 x 2.62 in) Weight- packed: 952 g (2.09 lb)- product only: 785 g (1.73 lb) Installation- DIN rail mounting Ambient conditions Operating temperature- -40 to 85°C (-40 to 185°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV- IEC 61000-4-5 Surge: Power: 4 kV; Signal: 4 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 10 V/m- IEC 61000-4-8 PFMF- IEC 61000-4-11 Environmental testing- IEC 60068-2-1- IEC 60068-2-14- IEC 60068-2-2- IEC 60068-2-3 Safety- EN 62368-1, UL 62368-1, UL 60950-1 Vibration- IEC 60068-2-6 Power Substation- IEC 61850-3 MTBF Time- 4.660,534 hrs Standards- Telcordia SR332

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

