

Item no.: 385772

NE-4110S - Device server module for RS-232 devices, supports 10/100BaseT(x) with RJ45 connection

from **75,53 EUR**

Item no.: 385772
 shipping weight: 0.10 kg
 Manufacturer: MOXA



Product Description

Device server module for RS-232 devices, supports 10/100BaseT(x) with RJ45 connection
 Platform CPU- 16-bit MCUMemoryFlash- 2 MBSDRAM- 1 MBInput/output interfaceConfigurable DIO channels (via software)- 4Ethernet interface10/100BaseT(X) ports, Auto MDI/MDI-X- 8-pin RJ45Magnetic isolation protection- 1.5 kV (built-in)Standards- IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X)- IEEE 802.3x for flow controlEthernet software functionsConfiguration options- Web console (HTTP), Windows utility, Telnet console, serial consoleManagement- ARP, Device Search Utility (DSU), DHCP client, HTTP, IPv4, SMTP, SNMPv1/v2c, TCP/IP, Telnet, UDP, web console, ICMPWindows Real COM driver- Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows 2008 R2/2012/2012 R2/2016/2019 (x64), Windows Embedded CE 5.0/6.0, Windows XP EmbeddedLinux Real TTY driver- Kernel versions: 2.4.x, 2.6.x, 3.x, 4.x and 5.xFixed TTY Drivers- SCO UNIX, SCO OpenServer, UnixWare 7, QNX 4.25, QNX 6, Solaris 10, FreeBSD, AIX 5.x, HP-UX 11i, Mac OS XAndroid API- Android 3.1.x and higherSerial InterfaceNo. Ports- 2 (1 for serial interface, 1 for TTL console port)Serial standards- RS-232Operating modes- Real COM mode, TCP client mode, TCP server mode, UDP modeBaud rate- 110 bps to 230.4 kbpsData bits- 5, 6, 7, 8Stop bits- 1, 1.5, 2Parity- None, Even, Odd, Space, MarkFlow control- None, RTS/CTS, DTR/DSR, XON/XOFFSerial signalsRS-232- Tx, Rx, RTS, CTS, DTR, DSR, DCD, GNDPerformance parametersInput voltage- 5 VDCCurrent consumption- 290 mA @ 5 VDCPhysical propertiesDimensions- 57 x 40 mm (2.24 x 1.57 in)Weight- 40 g (0.09 lb)Form factor type- Ready-to-use pin header modulesEnvironmental conditionsOperating temperature- 0 to 55°C (32 to 131°F)Storage temperature (including packaging)- -40 to 60°C (-40 to 140°F)Relative humidity- 5 to 95% (non-condensing)Standards and certificationsEMC- EN 55032/24EMI- CISPR 32, FCC Part 15B Class AEMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 1 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m- IEC 61000-4-8 PFMEnvironmental tests- IEC 60068-2-1- IEC 60068-2-3- IEC 60068-2-14DeclarationEnvironmentally friendly product- RoHS, CRoHS, WEEEEMTBFTime- 290.276 hoursStandards- Telcordia SR332

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

