

Item no.: 387952

## UPort 1250I - USB to 2-port RS-232/422/485 serial hub with 2 kV isolation

from **260,56 EUR**

Item no.: 387952  
 shipping weight: 0.70 kg  
 Manufacturer: MOXA



### Product Description

Moxa's UPort USB to Serial Converters provide computers with high-performance, industrial-grade connections for up to 16 serial devices over a single USB port. A wide range of converters are available with features such as SuperSpeed USB 3.2 and Hi-Speed USB 2.0, advanced UARTs for high serial performance, COM port mapping, fixed-base COM functionality and more. Serial hub with 2 ports for RS-232/422/485 with 2 kV isolation USB interface Speed- 12 Mbps, 480 Mbps USB port- USB Type B USB standards- USB 1.1/2.0 compliant Serial interface Number of ports- 2 Connector- DB9 male Baud rate- 50 bps to 921.6 kbps Data bits- 5, 6, 7, 8 Stop bits- 1, 1.5, 2 Parity- None, Even, Odd, Space, Mark Flow control- None- RTS/CTS- XON/XOFF Isolation- 2 kV Serial standards- RS-232/422/485 (DB9 connector) Serial signals RS-232- Tx+, Rx+, RTS, CTS, DTR, DSR, DCD, GND RS-422- Tx+, Tx-, Rx+, Rx-, GND RS-485- 4w- Tx+, Tx-, Rx+, Rx-, GND RS-485- 2w- Data+, Data-, GND Serial software functions Windows driver- Windows 11/10/8.1/8/7/Vista/XP/ME/98/95- Windows Server 2022/2019/2016/2012 R2/2012/2008 R2/2008/2003/2000/NT Linux driver- Kernel versions: 6.x, 5.x, 4.x, 3.x, 2.6.x and 2.4.x Mac driver- macOS versions: 10.12 to 10.15, 11.x Virtual machine- VMware Fusion (Windows on macOS 10.12 to 11.x)- VMWare ESXi (Linux Kernel 4)- Parallels Desktop (Windows on macOS 10.12 to 11.x) Support for Arm®-based platforms- Linux Kernel 5.x / 4.x Android API- Android 3.1.x and higher Performance parameters Input voltage- 12 to 48 VDC Input current- 200 mA @ 12 VDC Physical characteristics Housing- Metal Dimensions- 77 x 26 x 111 mm (3.03 x 1.02 x 4.37 in) Weight- 680 g (1.5 lb) Environmental conditions Storage temperature (including packaging)- -20 to 75°C (-4 to 167°F) Relative humidity- 5 to 95% (non-condensing) Operating temperature- 0 to 60°C (32 to 140°F) Standards and certifications EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV- IEC 61000-4-5 Surge: Power: 1 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m- IEC 61000-4-8 PFM Safety- UL 60950-1 Declaration Environmentally friendly product- RoHS, CROHS, WEEE MTBF Time- 563,179 hours Standards- Telcordia (Bellcore) Standard

### Specifications

Scan this QR code to  
 view the product  
 All details, up-to-date  
 prices and availability

