

Item no.: 385702

## VPOR 06-2M36M - EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 built-in microphone

from **765,88 EUR**

Item no.: 385702  
shipping weight: 0.70 kg  
Manufacturer: MOXA



### Product Description

Our range of IP cameras includes dome and box cameras as well as cameras with a robust design. They fulfil parts of the EN 50155 standard and therefore offer reliable performance and excellent image quality for a range of applications. EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 microphone built-in, 24 VDC, 3.6 mm lens, -25 to 55°C operating temperature, Memory/microSD slot- SDXC Input/output interface Digital input channels- 1 Digital inputs- +13 to +30 V for state 1- -30 to +1 V for state 0- Max. Input current: 8 mA Connector- DB9 connector Ethernet interface 10/100BaseT(X) ports (M12 D-coded 4-pin socket)- 1 Ethernet- Software functions/Protocols- TCP/IP- IPv4/IPv6- UDP- HTTP- RTP/RTSP- ARP- UPnP- FTP- TFTP- NTP- Client- DNS NTP Client- DNS- QoS- IGMP v3- ICMP- SNMPv1/v2c/v3- DHCP Opt66/67- HTTPS- SIP Security functions Password- Password protection at user level Filter- IP-address Encryption- HTTPS- SSH Performance parameters Number of power inputs- 1 Input voltage- 12/24 VDC Input current- 0.86 A @ 12 VDC, 0.35 A @ 24 VDC Power connection- DB9 connector Camera features Sensor- 1/3-in 1080P progressive scan CMOS Lens- f=3.6 mm, F1.6, diagonal 99°, horizontal 70°, vertical 39° Minimum illumination- Colour: 0.2 lux, at F1.2 (gain high, 50 IRE, 1/30 sec.) Synchronisation- Internal White balance- ATW/AWB Electronic shutter- Auto, fixed (1/30 to 1/25000 sec.) Signal-to-noise ratio- Maximum 50 dB (AGC off; DNR on) DNR (Digital Noise Reduction)- Built-in 2D/3D DNR WDR (Wide Dynamic Range)- 100 dB AGC (Automatic Gain Control)- 2X, 4X, 8X, 16X Flickerless Control- Automatic, 50 Hz, 60 Hz modes Image rotation- Flip, Mirror, 90°, 180°, 270° rotation Image adjustment- Manual adjustment with saturation, sharpness and contrast Camera angle- Pan: ±15°, tilt: 0° to 90° (manually controlled) Video interface Video compression- H.264 (ISO/IEC 14496-10) or MJPEG Video output- via Ethernet Video streams- 4 independent H.264 or MJPEG video streams Video resolution and FPS (frames per second) Video display- DynaStream™ support for automatically changing the video frame rate- CBR Pro™ for good image quality in transmissions with limited bandwidth- 3 areas for data protection masks- Adjustable image size and quality- Time stamp and text overlay- OSD (On Screen Display) position adjustable- Maximum 10 simultaneous unicast connections, 50 multicast clients Audio interface Audio format- Mono, PCM (G.711)- AAC Audio inputs- 1 x built-in microphone Camera software development Video standards- ONVIF Profile S Camera alarm software functions Intelligent video- Camera tampering detection Video motion detection Motion detection- 3 independently configurable areas Scheduling- Daily recurring schedule Imaging- JPEG snapshots for pre/trigger/post-alarm images Customised alarms- HTTP event server for setting custom alarm actions FTP messaging- Automatic transfer of saved images via FTP as event-triggered actions Pre-alarm buffer- 50 MB video buffer for JPEG images 50 MB video buffer for JPEG snapshots Video recording- Event recordings on SD card Software requirements Memory size- 2 GB Operating system- Windows 7 or higher Browser- Internet Explorer 9.x or higher Multimedia- DirectX 9.0C or higher Physical properties Housing- IP66 rain and dust protection Metal housing, PC dome cover- IK8 vandal-proof Dimensions- 110 x 115.5 x 61.8 mm (4.33 x 4.53 x 2.43 in) Weight- 620 g (1.37 lb) Installation- Panel mounting Protection- PCB conformal coating is optional and will be provided on request. If conformal coating is required, please contact Moxa. Environmental conditions Operating temperature- -25 to 55°C (-13 to 131°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Ingress protection- IEC 60529, IP66 Vandal resistance- EN 62262, IK8 Altitude- 2000 m- Note: Please contact Moxa if you require products that are guaranteed to work perfectly at higher altitudes. Standards and certifications EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFM Free fall- IEC 60068-2-31 Railway fire protection- EN 45545-2 Safety- UL 62368-1 Shock- IEC 60068-2-27, IEC 61373, EN 50155 Vibration- IEC 60068-2-64, IEC 61373, EN 50155 Railway- EN 50155 (fulfils part of the EN 50155 specifications) MTBF Time- 1.039,008 hours Standards- Telcordia SR332

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

