

Item no.: 385609

NPORT 5610-8 - 8-port RS-232 rackmount device server with RJ45 connections and 100 to 240 VAC

from **709,83 EUR**

Item no.: 385609
shipping weight: 2.30 kg
Manufacturer: MOXA



Product Description

8-port RS-232 rackmount device server with RJ45 connectors and 100 to 240 VAC power input Ethernet interface 10/100BaseT(X) ports (RJ45 connector)- 1Magnetic isolation protection- 1.5 kV (built-in) Ethernet software functions Configuration options- Telnet console- Web console (HTTP/HTTPS)- Windows utility Administration- ARP- BOOTP- DHCP client- DNS- HTTP- HTTP DNS- HTTP- HTTP- HTTPS- ICMP- IPv4- LLDP- RFC2217- Rtelnet- PPP- SLIP- SMTP- SNMPv1/v2c- TCP/IP- Telnet- UDP Filter- IGMP v1/v2c Windows Real COM Drivers- Windows 11/10/8.1/8/7/Vista/XP/ME/98/95- Windows Server 2022/2019/2016/2012 R2/2012/2008 R2/2008/2003- Windows Embedded CE 6.0/5.0, Windows XP Embedded Linux Real TTY Drivers- Kernel versions 6.x, 5.x, 4.x, 3.x, 2.6.x, and 2.4.x Fixed TTY Drivers- macOS Versions: 11.x, 10.12 to 10.15 Support for Arm@-based platforms- Linux Kernel 5.x/4.x Virtual Machine- VMWare ESXi (Windows 11/10)- VMware Fusion (Windows on macOS 10.12 to 11.x)- Parallels Desktop (Windows under macOS 10.12 to 11.x) Android API- Android 3.1.x and higher Time management- Sntp Security functions Authentication- Local database Encryption- HTTPS- AES-128- RSA-1024- SHA-1- SHA-256 Security protocols- HTTPS (TLS 1.2)- SNMPv3 Serial interface Connection- 8-pin RJ45 Nos. Ports- 8 Serial standards- RS-232 Operating modes- Disabled- Ethernet modem- Pair connection- Real COM- Reverse Telnet- RFC2217- TCP Client- TCP Server- UDP Baud rate- Supports standard baud rates (unit=bps): 50, 75, 110, 134, 150, 300, 600, 1200, 1800, 2400, 4800, 7200, 9600, 19200, 38400, 57600, 115200, 230.4k, 460.8k, 921.6k Data bits- 5, 6, 7, 8 Stop bits- 1, 1.5, 2 Parity- None, Even, Odd, Space, Mark Flow control- None- RTS/CTS (RS-232 only)- DTR/DSR (RS-232 only)- XON/XOFF Terminating resistor for RS-485- 120 Ohm RS-485 data direction control- Automatic data direction control (ADDC) Serial signals RS-232- Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND Performance parameters Input current- 141 mA @ 100 VAC Input voltage- 100 to 240 VAC, 47 to 63 Hz Reliability Automatic reboot trigger- Built-in WDT Physical characteristics Housing- Metal Installation- 19-inch rack mount Dimensions (with ears)- 480 x 45 x 198 mm (18.90 x 1.77 x 7.80 in) Dimensions (without ears)- 440 x 45 x 198 mm (17.32 x 1.77 x 7.80 in) Weight- 2,290 g (5.05 lb) Interactive interface- LCD display- Push buttons for configuration Environmental conditions Operating temperature- 0 to 60°C (32 to 140°F) Storage temperature (including packaging)- -20 to 70°C (-4 to 158°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD- Contact: 8 kV; Air: 15 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m- IEC 61000-4-4 EFT: Power: 4 kV; Signal: 2 kV- IEC 61000-4-5 Surge: Power: 2.5 kV; Signal: 1 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m- IEC 61000-4-8 PFMF- IEC 61000-4-11 Safety- UL 62368-1 Medical- EN 55011: 2007+A2: 2007 Class A (Group 1) compliant- EN 60601-1-2: 2007 compliant MTBF Time- 903,009 hours Standards- MIL-HDBK-217F

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

