

Item no.: 385956

## VPORT P06-1MP-M12-MIC-CAM36-T - EN50155, HD, compact IP camera, M12 connection, 1 microphone, PoE

from **730,15 EUR**

Item no.: 385956  
shipping weight: 0.40 kg  
Manufacturer: MOXA



### Product Description

Our range of IP cameras includes dome and box cameras as well as cameras with a robust design. They fulfil parts of the EN 50155 standard, providing reliable performance and excellent image quality suitable for a range of applications. EN50155, HD, compact IP camera, M12 connection, 1 audio input, PoE, 3.6 mm lens, -40 to 70°C operating temperature Ethernet interface- PoE ports (10/100BaseT(X), M12 D-coded 4-pin female connector) 1 Ethernet Software Features- Protocols TCP/IP IPv4 UDP HTTP RTP/RTSP ARP UPnP FTP TFTP NTP Client DNS QoS IGMP v3 ICMP SNMP v1/v2c/v3 DHCP Opt66/67 HTTPS Security Functions- User-level password protection - Password protection Password User-level password protection- Filter IP address- Encryption HTTPS Power Parameters- No. of Power Inputs 1- Source of Input Power PoE (IEEE 802.3af)- Input Current 0.12 A @ 48 VDC Camera Characteristics- Sensor 1/2.7-in HD progressive scan CMOS- Lens f=3.6 mm, F1.6, Diagonal 99°, Horizontal 94°, Vertical 47°- Camera Angle Pan: ±30°, Tilt: 0° to 90° (controlled manually)- Minimum Illumination Colour: 0.2 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec)- Synchronisation Internal- White Balance ATW/AWB- Electronic Shutter Auto, Fixed (1/30 to 1/25000 sec)- S/N Ratio Maximum 50 dB (AGC off; DNR on)- DNR (digital noise reduction) Built-in 2D/3D DNR- WDR (wide dynamic range) 110 dB- Flickerless Control Automatic, 50 Hz, 60 Hz modes- Image Rotation Flip, Mirror, and 180° rotation- Image Setting Manual tuning with saturation, sharpness, and contrast- AGC (auto gain control) 2X, 4X, 8X, 16X, 32X, 64X- BLC (back light compensation) High/Medium/Low Video Interface- Video Compression H.264 (ISO/IEC 14496-10) or MJPEG- Video Output via Ethernet- Video Streams 3 independent H.264 or MJPEG video streams- Video Resolution and FPS (frames per second) Read more- Video Viewing DynaStream™ support for changing the video frame rate automatically CBR Pro™ for good image quality in limited bandwidth transmissions 3 privacy mask areas provided Adjustable image size and quality Timestamp and text overlay OSD (On Screen Display) position adjustable Maximum of 5 simultaneous unicast connections, 50 multicast clients Audio Interface- Audio Inputs 1 x line-in, with RCA connector- Audio Format Mono, PCM (G.711) Camera Software Development- Video Standards ONVIF Profile S Camera Alarm Software Features- Intelligent Video Camera tampering detection- Video Motion Detection 3 independently configurable areas- Scheduling Daily repeat timing schedule- Imaging JPEG snapshots for pre/trigger/post alarm images- Custom Alarms HTTP event servers for setting customised alarm actions- FTP Messaging Automatic transfer of stored images via FTP as event-triggered actions Software Requirements- Memory Size 1 GB- Operating System Windows 7 or above- Browser Internet Explorer 9.x or above- Multimedia Direct X 9.0C or above Physical Characteristics- Housing Plastic top cover, metal bottom plate IP66 rain and dust protection IK10 vandal resistant protection Transparent PC cover- Dimensions 110 x 47 mm (4.33 x 1.85 in)- Weight 310 g (0.68 lb)- Installation Panel mounting Environmental Limits- Operating Temperature -40 to 70°C (-40 to 158°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing)- Ingress Protection IEC 60529, IP66- Vandal Resistance EN 62262, IK10- Altitude 2000 m Standards and Certifications- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Signal: 2 kV IEC 61000-4-5 Surge: Signal: 1 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Freefall IEC 60068-2-31- Railway Fire Protection EN 45545-2- Safety UL 62368-1- Shock IEC 60068-2-27, IEC 61373, EN 50155- Vibration IEC 60068-2-64, IEC 61373, EN 50155- Railway EN 50155 (complies with a portion of EN 50155 specifications) MTBF- Time 1,944,687 hrs- Standards Telcordia SR332

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

