

Item no.: 387623

SFP-10GSRLC-T - SFP module with 1 10GBase-SR port, LC connection

from **1.229,82 EUR**

Item no.: 387623
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

SFP+ module with 1 10GBase-SR port, LC connector for 33m/82m/300m/400m transmission, -40 to 85°C operating temperature
Ethernet Interface Connector- Duplex LC connector
Optical Fiber- Typical distance: To achieve the typical distance of the specified fibre optic transceiver, please observe the formula: $\text{Link Budget(dB)} > \text{Dispersion Loss(dB)} + \text{Total Loss(dB)}$
Environmental Conditions
Operating Temperature- -40 to 85°C (-40 to 185°F)- Note: When using the SFP-10GSRLC-T with the ICS-G7526A/G7528A/G7826A/G7828A and the MDS-G4000-4XGS/MDS-G4000-L3-4XGS series, the maximum temperature is -10 to 60°C (14 to 140°F).
Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F)
Relative humidity of the environment- 5 to 95% (non-condensing)
Standards and certifications
Safety- UL 62368-1- IEC 62368-1- IEC 60825-1
EMC- EN 55032/35
EMI- FCC 15B Test Report- ICES-003: 2020 Edition
7EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV(AC), 0.5 kV(DC); Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 1 kV/2 kV(AC), 0.5 kV(DC); Signal: 1 kV- IEC 61000-4-6 CS: 0.15 MHz to 10 MHz: 3 V, 10 MHz to 30 MHz: 3 to 1 V, 30 MHz to 80 MHz: 1 V.- IEC 61000-4-8 PFMF: 1 A/m at 50 Hz- IEC 61000-4-11: Voltage dips and interruptions

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

