

Item no.: 386197

PTC-101-S-LC-LV - Industrial 10/100BaseT(X) to 100BaseFX media converter

from **663,47 EUR**

Item no.: 386197
shipping weight: 1.00 kg
Manufacturer: MOXA



Product Description

Industrial 10/100BaseT(X) to 100BaseFX media converter, singlemode with LC connector, two redundant power inputs (20 to 70 VDC), -40 to 85°C Operating temperature Ethernet interface 10/100BaseT(X) ports (RJ45 connector)- 1 100BaseFX ports (singlemode LC connector)- 1 Magnetic isolation protection- 1.5 kV (built-in) Performance parameters Input voltage- 20 to 72 VDC Input current- 150 mA @ 20 VDC Overload current protection- Supported Current consumption- 150 mA @ 20 VDC Physical characteristics Housing- Metal Dimensions- 152.15 x 126.46 x 66.65 mm (5.99 x 4.86 x 2.62 in) Weight- packed: 952 g (2.09 lb)- product only: 785 g (1.73 lb) Installation- DIN rail mounting Environmental conditions Operating temperature-40 to 85°C (-40 to 185°F) Storage temperature (including packaging)-40 to 85°C (-40 to 185°F) Relative humidity 5 to 95% (non-condensing) Standards and certifications EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV- IEC 61000-4-5 Surge: Power: 4 kV; Signal: 4 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 10 V/m- IEC 61000-4-8 PFMF- IEC 61000-4-11 Environmental testing- IEC 60068-2-1- IEC 60068-2-14- IEC 60068-2-2- IEC 60068-2-3 Safety- EN 62368-1, UL 62368-1, UL 60950-1 Vibration- IEC 60068-2-6 Power Substation- IEC 61850-3 MTBF Time- 4.660,534 hours Standards- Telcordia SR332

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

