

Item no.: 387957

UPOINT 1450-G2-T - USB to 4-port RS-232/422/485 converter, -40 to 75C operating temperature

from **333,43 EUR**

Item no.: 387957
shipping weight: 0.40 kg
Manufacturer: MOXA



Product Description

Moxa's UPort USB-to-serial converters provide computers with high-performance, industrial-grade connections for up to 16 serial devices over a single USB port. A wide range of converters is available with features such as SuperSpeed USB 3.2 and Hi-Speed USB 2.0, advanced UARTs for high serial performance, COM port mapping, fixed-base COM functionality and more.

USB to 4-port RS-232/422/485 converter, -40 to 75°C operating temperature

USB Interface- USB Standards USB 3.2 Gen 1 USB 1.1/2.0 compliant- Speed 5 Gbps, 480 Mbps, 12 Mbps- No. of USB Ports 1- USB Connector USB Type B Serial Interface- Connector DB9 male- No. of Ports 4- Serial Standards RS-232/422/485- FIFO 512 bytes- Baudrate 50 bps to 921.6 kbps (supports non-standard baudrates)- Parity None, Even, Odd, Space, Mark- Data Bits 5, 6, 7, 8- Stop Bits 1, 1.5, 2- Flow Control RTS/CTS, XON/XOFF- RS-485 Data Direction Control Automatic Data Direction Control (ADDC)- Pull High/Low Resistor for RS-485 1 kilo-ohm, 150 kilo-ohms- Terminator for RS-485 120 ohms- Surge 0.5 kV- Isolation 2 kV (I models) Serial Signals- RS-232 Tx+, Rx+, RTS, CTS, DTR, DSR, DCD, GND- RS-422 Tx+, Tx-, Rx+, Rx-, GND- RS-485-4w Tx+, Tx-, Rx+, Rx-, GND- RS-485-2w Data+, Data-, GND

Serial Software Features- Windows Drivers Windows 11, 10, 8.1, 8 and 7 Windows Server 2022, 2019, 2016, 2012 R2, 2012 and 2008 R2- Linux Drivers Kernel 6.x, 5.x and 4.x- Mac Drivers macOS version (Intel 64): 13, 12, 11 and 10.1x- Virtual Machine VMware Fusion (Windows on macOS 13, 12, 11, 10.1x, Intel 64) VMware ESXi (Linux kernel 4) Parallels Desktop (Windows on macOS 13, 12, 11, 10.1x, Intel 64)- Arm®-based Platform Support Linux kernel 6.x, 5.x and 4.x- Android API Android 3.1.x and later

Power Parameters- Input Voltage 5 VDC by USB bus power or 12 to 48 VDC by external power adaptor- Input Current 266 mA @ USB 2.0 452 mA @ USB 3.2 240 mA @ 12 VDC

Physical Characteristics- Housing Metal- Dimensions 185 x 30 x 90.6 mm (7.28 x 1.18 x 3.57 in)- Weight 373 g (0.82 lb)- IP Rating IP20

Environmental Limits- Operating Temperature -40 to 75°C (-40 to 167°F)- Storage Temperature -40 to 75°C (-40 to 167°F)- Ambient Relative Humidity 5 to 95% (non-condensing)

Standards and Certifications- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV IEC 61000-4-5 Surge: Power: 1 kV, Signal: 0.5 kV IEC 61000-4-6 CS: 3 V; 150 kHz to 80 MHz IEC 61000-4-8 PFMF- Safety IEC 62368-1 EN 62368-1 UL 62368-1 (CB) KC- Shock IEC 60068-2-27- Vibration IEC 60068-2-6 IEC 60068-2-64- Freefall IEC 60068-2-31 Declaration- Green Product RoHS, CRoHS, WEEE MTBF- Standards Telcordia Standard SR332, Telcordia Issue 2- Time 1,431,860 hrs

Specifications

Scan this QR code to view the product
All details, up-to-date prices and availability

