

Item no.: 384352

QuOmni 5GLTE Global MIMO 2x2, 10m



from **113,95 EUR**

Item no.: 384352
 shipping weight: 1.60 kg
 Manufacturer: QuWireless

Product Description

Omnidirectional ultra wideband 5G/LTE MIMO 2x2 antenna QuOmni 5G/LTE omnidirectional MIMO 2x2 is ultra wideband LTE Outdoor antenna. It's primary designed for LTE/5G/3G/2G devices which require high efficiency connections. The antenna covers many LTE bands including the new Extended LTE Band 71, frequencies: 617 - 6000MHz. The mounting bracket allows the antenna to be installed on the buildings (on the pole or on the wall) as the client antenna or on the moving points like trains, buses, lorries, yachts, boats to receive Internet by LTE/5G/3G/2G. It's ideal solution to use with all industrial and domestic 2x2 LTE modems and routers like: Teltonika, DIGI, Mikrotik, Robustel, Cisco, etc.

5G / LTE ANTENNA SPECIFICATION - Frequency 617 - 960 MHz 1.7 - 2.7 GHz 3.3 - 4.7 GHz 5.2 - 6.0 GHz - Gain 617 - 960 MHz : 3 dBi 1.7 - 2.7 GHz : 4 dBi 3.3 - 4.7 GHz : 4.5 dBi 5.2 - 6.0 GHz : 2.5dBi - Supported LTE bands 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 47, 48, 49, 52, 53, 65, 66, 67, 8, 69, 71, 85, 103, 106 - Supported 5G bands n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n47, n48, n53, n65, n66, n67, n71, n77, n78, n80, 81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n98, n100, n101, n256 - VSWR <1.80, max <2.00 - Beamwidth 360°/35° ±5° - Polarization Vertical - Impedance 50 Ω

MECHANICAL SPECIFICATION - Materials ABS, aluminum, PTFE - Connector type SMA - Ingress protection IP67 - Dimensions 160 x 160 x 240 mm 6.3 x 6.3 x 9.45 inch - Weight 1.5 kg 3.31 lbs - Operating temperature From -40°C to 80°C From -40°F to 176°F - Mast diameter 40-60 mm 1.57-2.36 inch

Specifications

Scan this QR code to
 view the product

All details, up-to-date
 prices and availability

