

Item no.: 384317

QuMax for Peplink MAX BR1 Pro 5G CAT-20

from **235,23 EUR**

Item no.: 384317
 shipping weight: 2.00 kg
 Manufacturer: QuWireless



Product Description

INTEGRATED MULTI-BAND 5G DIRECTIONAL ANTENNA + WIFI OMNI ANTENNA + GPS ANTENNA + PLACE TO INSTALL PEPLINK MAX BR1 PRO 5G & CAT-20 (ALL-IN-ONE) QuMax all-in-one antenna for Peplink MAX BR1 Pro 5G & CAT-20 router is dedicated to connections with long distance to base station. It has embedded directional 5G, Wi-Fi and GPS antenna. If you use MAX BR1 Pro 5G or CAT-20 with QuMax Omni antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure. It is the first choice for fixed installations in industrial environment. The set contains a Passive PoE splitter, allowing you to split data and power from a single Ethernet cable and maintain gigabit transfer speeds while protecting the LAN port from damage caused by overvoltage, short circuit or improper connection.

5G/LTE SPECIFICATION - FREQUENCY 617 - 960 MHz : 1.7 - 2.7 GHz : 3.3 - 4.6 GHz : 4.7 - 6.0 GHz - **SUPPORTED LTE BANDS** 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 46, 47, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 06 - **SUPPORTED 5G BANDS** n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n46, n47, n48, n53, n65, n66, n67, n71, n77, n78, n79, n80, n81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n98, n100, n101, n256 - **GAIN** 617 - 960 MHz : 6 dBi : 1.7 - 2.7 GHz : 7 dBi : 3.3 - 4.6 GHz : 7 dBi : 4.7 - 6.0 GHz : 5.5 dBi - **VSWR** < 2.00, max < 3.00 - **BEAMWIDTH** 80°/80° ±15° - **POLARIZATION** Vertical - **IMPEDANCE** 50 Ω - **WI-FI SPECIFICATION - FREQUENCY** 2.4 - 2.5 GHz : 5.0 - 7.2 GHz - **GAIN** 2.4 - 2.5 GHz : 6dBi : 5 GHz : 7.5dBi : 7 GHz : 7.5dBi - **VSWR** < 1.50, max < 2.00 - **BEAMWIDTH** 360°/25° +/- 5° - **POLARIZATION** Vertical - **IMPEDANCE** 50 Ω - **MECHANICAL SPECIFICATION - MATERIAL** BS, aluminum, PTFE, Fiberglass - **INGRESS PROTECTION** IP67 - **CONNECTOR TYPE** RJ45 - **DIMENSIONS** 486.0 x 292.2 x 210 mm : 19.13 x 11.50 x 8.27 inch - **WEIGHT** 1.8 kg : 3.97 lbs - **OPERATING TEMPERATURE** From -40°C to 75°C : From -40°F to 167°F - **MOUNTING KIT - DIMENSIONS** 9.9 x 10.5 x 14.8 cm : 3.9 x 4.13 x 5.83 inch - **REGULATION RANGE** +/- 30° - **MAST DIAMETER RANGE** 25 - 60mm : 0.98-2.36 inch - **MATERIAL** Polyamide with fiberglass + galvanized steel U-Bolts - **WEIGHT** 0.87kg - **MOUNTING PLACE** Wall or mast or ceiling

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

