

Item no.: 389308

## MS138C - 13 in 8 cast multi-switch NEVO, casc. without NT (MS-NT1228)

from **232,76 EUR**

Item no.: 389308  
shipping weight: 0.80 kg  
Manufacturer: Televes



### Product Description

Multi-switch with 13 inputs (1 x terrestrial and 12 x SAT) and 8 subscriber outputs. Very flexible: Can be used as a single or cascade switch thanks to switchable terminating resistors. Highlights- Attenuation switch 10dB for the subscribers (ON = LG / OFF = HG) for the SAT signal- Remote power supply via VL- DC pass-through between inputs and cascade outputs- Reverse channel compatible for CoaxData systems- European quality and design, 100% manufactured and tested at Televes Features- Very compact design- Cast housing developed and manufactured at Televes- Inputs and loop-through outputs colour-coded- Switching between cascade and single switch (terminating resistors can be added)- 12 V power supply- Low power consumption, therefore economical operation Specification- Number of inputs 13- Number of cascade outputs 13- Number of subscriber outputs 8- Frequency range TERR. MHz 88 ... 862- Frequency range SAT. MHz 950 ... 2400- Input level TERR. dB $\mu$ V 90- Input level SAT. dB $\mu$ V 112- Pass-through attenuation TERR. dB 2- Pass-through attenuation SAT. dB 2...5- Subscriber attenuation 1...8 TERR. dB 4- Subscriber attenuation 1...8 SAT. dB 3- Decoupling H/V dB > 30- TN decoupling dB > 25- Power supply Vdc 12- Max. Current consumption (PSU - LG) mA 40- Max. Current consumption (PSU - HG) mA 85- Max. Current consumption (STB) mA 40- Operating temperature °C -5 ... 45- Protection index 20

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

