

Item no.: 387761

SFP-1GZXLC-T - SFP module with 1 1000BaseZX port with LC connector for 80 km transmission

from **1.152,11 EUR**

Item no.: 387761
 shipping weight: 0.10 kg
 Manufacturer: MOXA



Product Description

Introduction The 1-port Gigabit Ethernet SFP modules of the SFP-1G series are available as optional accessories for a variety of Moxa Ethernet switches. Ethernet interface- Ports: 1- Connectors: Duplex LC connector, Simplex LC connector (WDM type only)- Optical fibre: Typical distance: To achieve the typical distance of the specified optical fibre transceiver, please refer to the formula: Link Budget(dB) > Stray Loss(dB) + Total Loss(dB) Performance Parameters- Power Consumption: Max. 1 W Environmental Limits Operating Temperature:- Standard Models: 0 to 60°C (32 to 140°F)- Wide Temp Models: -40 to 85°C (-40 to 185°F)- Storage Temperature (including packaging): -40 to 85°C (-40 to 185°F)- Ambient relative humidity: 5 to 95% (non-condensing) Standards and certifications Safety:- UL 62368-1- IEC 62368-1- IEC 60825-1- EMC: EN 55032/35 EMI:- FCC 15B Test Report- ICES-003: 2020 Edition 7 EMS:- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV(AC), 0.5 kV(DC); Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 1 kV / 2 kV(AC), 0.5 kV(DC); Signal: 1 kV- IEC 61000-4-6 CS: 0.15 MHz to 10 MHz: 3 V, 10 MHz to 30 MHz: 3 to 1 V, 30 MHz to 80 MHz: 1 V- IEC 61000-4-8 PFMF: 1 A/m at 50 Hz- IEC 61000-4-11 Voltage dips and interruptions- Marine: DNV

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

