

Item no.: 389259

MS512NCQ - 5 in 12 cast multi-switch NEVO with power supply unit, suitable for quads, casc.



from 170,62 EUR

Item no.: 389259 shipping weight: 0.90 kg Manufacturer: Televes

Product Description

Cascadable and QUAD-compatible multiswitch with 5 inputs (1x terrestrial and 4 polarities of a satellite) and 12 TN outputs. Can be used as a single multiswitch (star distribution) or as a cascade switch due to switchable terminating resistors. Highlights- Includes 12 V power supply unit MS-NT1208N (Ref. 732101)- Compatible with QUAD LNB due to 22KHz generator. - A switch for feeding terrestrial preamplifiers or for power feed-through. A switch for feeding terrestrial preamplifiers or for power feed-through. A switch for feeding terrestrial preamplifiers or for power feed-through. A switch for feeding terrestrial preamplifiers or for power feed-through. A switch for feeding terrestrial preamplifiers or for power feed-through. A switch for feeding terrestrial preamplifiers or for power feed-through. A switch for feeding terrestrial preamplifiers or for power feed-through. A switch for feeding terrestrial preamplifiers or for power feed-through. A switch for feeding terrestrial preamplifiers or for power feed via VL- DC curved in the power feed via VL- DC considerable termination properties. Colour coding of inputs and outputs to the top- Terrestrially active- European design, quality and manufactureFeatures- Very compact housing- Cast housing- with best shielding properties-Colour coding of inputs and outputs- ECO mode- Very flexible: Due to switchable terminating resistors to each individual or cascade switch- 12 V power supply- Low power consumption (receiver-powered) Specification- Number of inputs 5- Number of cascade outputs 5- Number of subscriber outputs 12- Frequency range TERR. MHz 47 ... 862- Frequency range SAT. MHz 950 ... 2400- Input level TERR. d8? 92- Input level SAT. d8?V 105- Pass-through attenuation TERR. d8 4- Subscriber attenuation 9...16 TERR. d8 4- Subscriber attenuation 9...16 SAT. d8 1- Subscriber attenuation 9...16 TERR. d8 4- Subscriber attenuation 9...16 SAT. d8 2- Decoupling H/V d8 > 30- TN decoupling d8 > 25- Power supply Vdc 12- Max. Current consumption (PSU) mA 85- Max. Current con

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

