

Item no.: 389316

MS516C - 5 in 16 cast multi-switch NEVO, receiverpowered, cascadable

from **174,70 EUR**

Item no.: 389316
shipping weight: 1.00 kg
Manufacturer: Teledes



Product Description

Cascadable multi-switch with 5 inputs (1 x terrestrial and 4 x SAT), 16 subscriber outputs, 5 loop-through outputs and a 12db level control at the subscriber outputs. Very flexible: Can be used as a single or cascade switch thanks to switchable terminating resistors. Highlights- One 12dB level control per subscriber to equalise the output level.- Switch for power supply to terrestrial and SAT systems. Switch for power supply of terr. Amplifier power supply switch- Power supply directly from receiver*- Remote power supply via V-Low input- DC pass-through between inputs and cascade outputs- Terrestrial power supply- European quality and design, 100% manufactured and tested at Teledes Features- Very compact- Cast housing designed and manufactured at Teledes- Inputs and loop-through outputs colour-coded- With ECO mode: Subscriber-dependent power consumption- Switching between cascade and single switch (terminating resistors can be switched on)- 12 V power supply- Low power consumption, therefore economical operation (receiverpowered) Specification- Number of inputs 5- Number of cascade outputs 5- Number of subscriber outputs 16- Frequency range TERR. MHz 47 ... 862- Frequency range SAT. MHz 950 ... 2400- Input level TERR. dB?V 92- Input level SAT. dB?V 105- Pass-through attenuation TERR. dB 4- Pass-through attenuation SAT. dB 3 ... 8- Subscriber attenuation 1...8 TERR. dB 2- Subscriber attenuation 1...8 SAT. dB 1- Subscriber attenuation 9...16 TERR. dB 4- Subscriber attenuation 9...16 SAT. dB 2- Level control per subscriber dB 0 ... 12- Decoupling H/V dB > 30- TN decoupling dB > 25- Power supply Vdc 12- Max. Current consumption (PSU) mA 105- Max. Current consumption (STB) mA 35- Operating temperature °C -5 ... 45- Protection index 20 Physical data- Net weight: 787 g- Gross weight: 787 g- Width: 137 mm- Height: 255 mm- Depth: 29 mm- Main product weight: 779 g Packaging- Carton 1 pc.

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

