

Item no.: 389399

MS516NG - 5 in 16 cast multi-switch MULTRIX with switching power supply unit

from **262,30 EUR**

Item no.: 389399
shipping weight: 1.50 kg
Manufacturer: Teledes



Product Description

QUAD-compatible multiswitch with 5 inputs (1x terrestrial and 4 polarities of a satellite), 16 TN outputs and with integrated power supply unit (single multiswitch). Highlights- LNB power supply via the integrated power supply unit- Compatible with Quad LNB Features- Compatible with other Teledes multiswitch families- Wall or top-hat rail mounting- Short-circuit proof Technical data- Outputs 47-2300 MHz MHz 16- Attenuation SAT typ. dB -8...-2- Attenuation terr. output 1-4 dB 0- Attenuation terr. output 5-8 dB -2- Attenuation terr. output 9-12 dB -3- Attenuation terr. output 13-16 dB -5- Max. Input level SAT dB?V 95- Max. Input level terr. dB?V 95- Current consumption per receiver mA 40- Switching voltage VL 14 V VH 14V 22KHz HL 18V HH 18V 22KHz- Output/output decoupling dB > 30- Ambient temperature °C -20 ... +50- Integrated switching power supply V 180-264 Physical data- Net weight: 1,308 grams- Gross weight: 1,623 grams- Width: 206 millimetres- Height: 219 millimetres- Depth: 65 millimetres- Main product weight: 1,182 grams

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

