

Item no.: 389400

MS524C - 5 in 24 cast multi-switch NEVO, receiverpowered, cascadable

from **275,54 EUR**

Item no.: 389400
shipping weight: 1.20 kg
Manufacturer: Televes



Product Description

Cascadable multi-switch with 5 inputs (1 x terrestrial and 4 x SAT), 24 subscriber outputs, 5 loop-through outputs and a 12db level control at the subscriber outputs. Very flexible: Can be used as a single or cascade switch thanks to switchable terminating resistors. Highlights- One 12dB level control per subscriber to equalise the output level.- Switch for power supply to terrestrial and SAT systems. Switch for power supply of terr. Amplifier power supply switch- Power supply directly from receiver*- Remote power supply via V-Low input- DC pass-through between inputs and cascade outputs- Terrestrial power supply- European quality and design, 100% manufactured and tested at Televes Features- Very compact- Cast housing designed and manufactured at Televes- Inputs and loop-through outputs colour-coded- With ECO mode: Subscriber-dependent power consumption- Switching between cascade and single switch (terminating resistors can be switched on)- 12 V power supply- Low power consumption, therefore economical operation (receiverpowered) Specification- Number of inputs 5- Number of cascade outputs 5- Number of subscriber outputs 24- Frequency range TERR. MHz 47 ... 862- Frequency range SAT. MHz 950 ... 2400- Input level TERR. dB?V 92- Input level SAT. dB?V 105- Pass-through attenuation TERR. dB 6- Pass-through attenuation SAT. dB 4.5 ... 12- Subscriber attenuation 1...8 TERR. dB 2- Subscriber attenuation 1...8 SAT. dB 1- Subscriber attenuation 9...16 TERR. dB 4- Subscriber attenuation 9...16 SAT. dB 2- Subscriber attenuation 17...24 TERR. dB 6- Subscriber attenuation 17...24 SAT. dB 5- Level control per subscriber dB 0 ... 12- Decoupling H/V dB > 30- TN decoupling dB > 25- Power supply Vdc 12- Max. current consumption (PSU) Current consumption (PSU) mA 175- Max. Current consumption (STB) mA 35- Operating temperature °C -5 ... 45- Protection index 20 Physical data- Net weight: 1,201 g- Gross weight: 1,201 g- Width: 137 mm- Height: 386 mm- Depth: 29 mm- Main product weight: 1,189 g Packaging- Carton 1 pc.

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

