


Item no.: 389271

MSE932C - 9 in 32 cast multi-switch EUROSITCH, casc. without NT (MS-NT1228)

from **587,25 EUR**

Item no.: 389271
shipping weight: 1.30 kg
Manufacturer: Teledes



Product Description

Compact multi-switch with 9 inputs (1 x terrestrial and 8 x SAT) and 32 subscriber outputs. Very low feed-through and branch attenuation due to its design. This means that the number of amplifiers required in a cascade can be reduced without compromising signal quality, even in large installations. Use as a single switch (star topology) or as a cascade switch. In addition, TForce technology can be activated so that the terrestrial signal automatically adjusts and remains constant despite reception fluctuations. RED compliant. Highlights- Very compact design and low weight, even for models with a high number of subscribers- Very low feed-through and branch attenuation- High decoupling between inputs and outputs- Equipped with TForce technology, this automatically adjusts the terrestrial output level (TERR. AMP. ACTIVE) is automatically set to the optimum level- 10 dB attenuation switch (Low Gain (LG) / High Gain (HG)) for each group of 8 subscriber outputs- Two power supply options: Either via a directly connected external power supply unit or, in a cascade connection, via the SAT connections- 100% European design, quality and manufacture Features- Very good shielding values: class A. Cast housing developed and manufactured by Teledes- Very flexible: Due to switchable terminating resistors to any single or cascade switch- Low power consumption in normal operation. In addition, there is an ECO mode in which the power consumption decreases as the number of connected users decreases- 12-18V power supply range- Current circulation between all inputs and cascades- Inputs and loop-through outputs colour-coded Specification- Number of inputs 9- Number of cascade outputs 9- Number of subscriber outputs 32- Frequency range TERR. MHz 88 ... 862- Frequency range SAT. MHz 950 ... 2400- Input level TERR. dBµV 80 ... 110- Input level SAT. dBµV 65 ... 112- Pass-through attenuation TERR. dB < 5- Pass-through attenuation SAT. dB 4 ... 6.5- Subscriber attenuation TERR. Active dB 3- Subscriber attenuation TERR. Passive dB 35- Subscriber attenuation SAT. HG dB 0- Subscriber attenuation SAT. LG dB 14 ... 8- Output voltage 10Ch DVB-T dBµV 78- Decoupling H/V dB > 50- TN decoupling dB > 30- Power supply Vdc 12 ... 18- Max. Current consumption (PSU - TERR ACT.) mA 115 *1- Max. Current consumption (PSU - TERR PAS.) mA 5- Max. Max. current consumption (STB) mA 85- Operating temperature °C -5 ... 45- Protection index (IP) 20 Physical data- Net weight: 1,221 g- Gross weight: 1,221 g- Width: 210 mm- Height: 353 mm- Depth: 45 mm- Main product weight: 1,221 g

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

