

Item no.: 385742

## VPORT P16-2MR36M-T - EN50155, day/night, IR, 1080P IP camera

from **1.025,48 EUR**

Item no.: 385742  
shipping weight: 0.90 kg  
Manufacturer: MOXA



### Product Description

Our range of IP cameras includes dome and box cameras as well as cameras with a robust design. They fulfil parts of the EN 50155 standard, providing reliable performance and excellent image quality suitable for a range of applications. EN50155, day & night, IR, 1080P IP camera, 3.6 mm lens, PoE, M12 connector, -40 to 70°C operating temperature. Memory - microSD Slot: SDXC Input/Output Interface - Digital Input Channels: 1 - Digital Inputs: +13 to +30 V for state 1, -30 to +1 V for state 0, Max. input current: 8 mA - Digital Inputs: +13 to +30 V for state 1, -30 to +1 V for state 0, Max. input current: 8 mA - Connector: 5-pin A-coded male M12 connector with 20 cm cable Ethernet Interface - PoE Ports (10/100BaseT(X), M12 D-coded 4-pin female connector): 1 - Standards: IEEE 802.3af for PoE Ethernet Software Features - Protocols: TCP/IP, IPv4/IPv6, UDP, HTTP, RTP/RTSP, ARP, UPnP, FTP, TFTP, SMTP, NTP Client, DNS, DDNS, QoS, IGMP v3, ICMP, SNMP v1/v2c/v3, DHCP Opt66/67, HTTPSSecurity Functions - Password: User-level password protection - Filter: IP address - Encryption: HTTPS Power Parameters - No. of Power Inputs: 1 - Source of Input Power: PoE (IEEE 802.3af) - Input Current: 0.26 A @ 48 VDC Camera Characteristics - Sensor: 1/3-in 1080P progressive scan CMOS - Lens: f=3.6 mm, F1.6, Diagonal 99°, Horizontal 70°, Vertical 39° - Minimum Illumination Colour: 0.2 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec) B/W: 0.05 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec) Note: 0 lux if IR illuminator is on - Camera Angle: Pan 350°, Tilt 65° (controlled manually) - Day & Night: Auto/Color/BW; ICR control - Synchronisation - Internal: White Balance - ATW/AWB: Electronic Shutter - Auto, Fixed (1/30 to 1/25000 sec) - S/N Ratio: Maximum 50 dB (AGC off; DNR on) - ICR Control: Auto (light sensor control) or DI control - IR Illumination: IR LED illuminators, 5-metre (max.) effective distance; On/Off controlled manually (night mode) or by the light sensor - DNR (digital noise reduction): Built-in 2D/3D DNR - WDR (wide dynamic range): 100 dB - AGC (auto gain control): 2X, 4X, 8X, 16X - Flickerless Control: Automatic, 50 Hz, 60 Hz modes - Image Rotation: Flip, Mirror, 90°, 180°, 270° rotation - Image Setting: Manual tuning with saturation, sharpness, and contrast - Video Interface - Video Compression: H.264 (ISO/IEC 14496-10) or MJPEG - Video Output: via Ethernet - Video Streams: 4 independent H.264 or MJPEG video streams - Video Viewing DynaStream™ support for changing the video frame rate automatically CBR Pro™ for good image quality in limited bandwidth transmissions 3 privacy mask areas provided Adjustable image size and quality Timestamp and text overlay OSD (On Screen Display) position adjustable Maximum of 5 simultaneous unicast connections, 50 multicast clients Audio Interface - Audio Format: Mono, PCM (G.711), AAC - Audio Inputs: 1 x built-in microphone Camera Software Development - Video Standards: ONVIF Profile S Camera Alarm Software Features - Intelligent Video: Camera tampering detection - Video Motion Detection: 3 independently configurable areas - Shock Detection: Built-in G sensor - Scheduling: Daily repeat timing schedule - Imaging: JPEG snapshots for pre/trigger/post alarm images - Custom Alarms: HTTP event servers for setting customised alarm actions - Email/FTP Messaging: Automatic transfer of stored images via email or FTP as event-triggered actions - Pre-Alarm Buffer: 50 MB video buffer for JPEG snapshot images - Video Recording: Event recordings stored on the SD card Software Requirements - Memory Size: 2 GB - Operating System: Windows 7 or above - Browser: Internet Explorer 9.x or above - Multimedia: DirectX 9.0C or above Physical Characteristics - Housing IP66 rain and dust protection Metal housing, PC dome cover IK8 vandal resistant protection - Dimensions: 125 x 125 x 120.7 mm (4.92 x 4.92 x 4.8 in) - Weight: 890 g (1.96 lb) - Installation: Panel mounting Environmental Limits - Operating Temperature: -40 to 70°C (-40 to 158°F) - Storage Temperature (package included): -40 to 85°C (-40 to 185°F) - Ambient Relative Humidity: 5 to 95% (non-condensing) - Ingress Protection: IEC 60529, IP66 - Salt Spray Test: ASTM-B117 - Vandal Resistance: EN 62262, IK8 - Altitude: 2000 m Standards and Certifications - EMI: CISPR 32, FCC Part 15B Class A - EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF - Freefall: IEC 60068-2-31 - Railway Fire Protection: EN 45545-2 - Safety: UL 60950-1 - Shock: IEC 60068-2-27, IEC 61373, EN 5015 - Vibration: IEC 60068-2-64, IEC 61373, EN 50155 - Railway: EN 50155 (complies with a portion of EN 50155 specifications) MTBF - Time: 997,474 hrs - Standards: Telcordia SR332

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

