

Item no.: 389328

MSE1708K - 17 in 8 cast multi-switch EUROSITCH, casc. without NT (MS-NT1228)

from **309,16 EUR**

Item no.: 389328
shipping weight: 0.90 kg
Manufacturer: Teledes



Product Description

Compact and effective for large installations Compact multi-switch with 17 inputs (1 x terrestrial and 16 x SAT) and 8 subscriber outputs. Very low feed-through and branch attenuation due to its design. This means that the number of amplifiers required in a cascade can be reduced without affecting the signal quality, even in large installations. Use as a single switch (star topology) or as a cascade switch. In addition, TForce technology can be activated so that the terrestrial signal automatically adjusts and remains constant despite reception fluctuations. Highlights- Very compact design and low weight, even for models with a high number of subscribers- Very low feed-through and branch attenuation- High decoupling between inputs and outputs- Equipped with TForce technology, which automatically adjusts the terrestrial output level (TERR. AMP. ACTIVE) to the optimum level- Two power supply options: Either via a directly connected external power supply unit or, in a cascade connection, via the SAT connections- 100% European design, quality and manufacture Features- Very good shielding values: class A. Cast housing developed and manufactured by Teledes- Very flexible: Due to switchable terminating resistors to any single or cascade switch- Low power consumption in normal operation. In addition, there is an ECO mode where the power consumption decreases as the number of connected users decreases- 12-18V power supply range- Current circulation between all inputs and cascades- Inputs and loop-through outputs colour-coded Technical specifications- Number of inputs: 17- Number of cascade outputs: 17- Number of subscriber outputs: 8- Frequency range TERR.: MHz 88 ... 862- SAT. frequency range: MHz 950 ... 2400- Input level TERR.: dBµV 80 ... 110- Input level SAT.: dBµV 65 ... 112- Pass-through attenuation TERR.: dB < 2- Pass-through attenuation SAT.: dB < 2- Subscriber attenuation TERR. Active: dB 0- Subscriber attenuation TERR. Passive: dB 32- Subscriber attenuation SAT.: dB 2 ... 7- Output voltage 10Ch DVB-T: dBµV 78- Decoupling H/V: dB > 50- TN decoupling: dB > 30- Power supply: Vdc 12 ... 18- Max. Current consumption (PSU - TERR ACT.): mA 65 *1- Max. Current consumption (PSU - TERR PAS.): mA 5- Max. Current consumption (STB): mA 85- Operating temperature: °C -5 ... 45- Protection index (IP): 20 Physical data- Net weight: 880g- Gross weight: 880g- Width: 350mm- Height: 120mm- Depth: 30mm- Main product weight: 880g

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

