

Item no.: 389933

## UOS15501310-9 - UOS15501310-9 - Optical transmitter 1550 terr.WDM 1310 sat., SCAPC 9dBm

from **465,18 EUR**

Item no.: 389933  
shipping weight: 0.50 kg  
Manufacturer: Televes



### Product Description

All TV and radio programmes from a satellite plus all DVB-T services via a fibre optic line. The FTTH transmitter receives an optical satellite signal (1310 nm) and a digital terrestrial signal modulated at 1550 nm, so that only one optical output is required to distribute all signals. Component of a complete system in combination with the optical receiver UOE15501310DIN (Ref. 237320).  
**Highlights-** Ideally suited for installations with a variety of DVB-T/T2 multiplexes.- Wide dynamic range  
**Features-** Supports dCSS and legacy multiswitches- Cast housing with very good shielding properties- Suitable for wall mounting- SC/APC optical connectors and F connectors for RFRF parameters- Frequency range: MHz 47 ... 2200- Ripple: dB  $\pm 0.75$  (47-1200MHz),  $\pm 2.5$  (47-1200MHz)- Input level: dB $\mu$ V 81 (47-1200MHz) 42ch CENELEC, 95 (950-2200MHz) DIB-VDE 0855/12- CNR/CSO/CTB: dB $\mu$ V  $>50$ / $>59$ / $>63$   
**Optical parameters-** Laser: Tipo MQW-DBF- Output power: dBm +9- Wavelength: nm 1550  
**General-** Supply voltage: V- 99...253- Max. Power consumption: W 2.5- Max. Current consumption: mA 75 (99V) / 45 (253V)- Dimensions: (xyz) mm 185 x 80 x 35- Weight: g 400- Protection class: IP 30  
**Physical data-** Net weight: 491g- Gross weight: 491g

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

