

Item no.: 389333

MSE58C - 5 in 8 cast multi-switch EUROSITCH, receiverpowered, cascadable

from **95,75 EUR**

Item no.: 389333
shipping weight: 0.50 kg
Manufacturer: Televes



Product Description

Compact multi-switch with 5 inputs (1 x terrestrial and 4 x SAT) and 8 subscriber outputs. Very low feed-through and branch attenuation due to its design. This means that the number of amplifiers required in a cascade can be reduced without compromising signal quality, even in large installations. Use as a single switch (star topology) or as a cascade switch. In addition, TForce technology can be activated so that the terrestrial signal is automatically adjusted and remains constant despite reception fluctuations. Highlights- Very compact design and low weight, even for models with a high number of subscribers- Very low feed-through and branch attenuation- High decoupling between inputs and outputs- Equipped with TForce technology, this automatically adjusts the terrestrial output level (TERR. AMP. ACTIVE) is automatically set to the optimum level- 10 dB attenuation switch (Low Gain (LG) / High Gain (HG)) for each group of 8 subscriber outputs- Multiple power supply options: Via a connected external power supply unit, in a cascade connection via the SAT connections or directly from the SAT receiver (RECEIVER POWER ACTIVE)- 100% European design, quality and manufacture Features- Very good shielding values: class A. Cast housing developed and manufactured by Televes- Very flexible: Due to switchable terminating resistors to any single or cascade switch- Low power consumption in normal operation. In addition, there is an ECO mode in which the power consumption decreases as the number of connected users decreases- 12-18V power supply range- Current circulation between all inputs and cascades- Inputs and loop-through outputs colour-coded Technical specifications- Number of inputs: 5- Number of cascade outputs: 5- Number of subscriber outputs: 8- Frequency range TERR.: MHz 88 ... 862- SAT. frequency range: MHz 950 ... 2400- Input level TERR.: dBµV 80 ... 110- Input level SAT.: dBµV 65 ... 112- Pass-through attenuation TERR.: dB < 2- Pass-through attenuation SAT.: dB < 2- Subscriber attenuation TERR. Active: dB 0 ... 4- Subscriber attenuation TERR. Passive: dB 32- Subscriber attenuation SAT.: HG dB 2 ... 7- Subscriber attenuation SAT.: LG dB 12 ... 14- Output voltage 10Ch DVB-T: dBµV 78- Decoupling H/V: dB > 50- TN decoupling: dB > 30- Power supply: Vdc 12 ... 18- Max. Current consumption (PSU - TERR ACT.): mA 65 *1- Max. Current consumption (PSU - TERR PAS.): mA 5- Max. Current consumption (STB): mA 85- Operating temperature: °C -5 ... 45- Protection index (IP): 20 Physical data- Net weight: 362g- Gross weight: 426g

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

