

Item no.: 389401

MS56NCQ - MS56NCQ - 5 in 6 cast multi-switch NEVO with power supply unit, suitable for quads, casc.

from 103,39 EUR

Item no.: 389401
shipping weight: 0.50 kg
Manufacturer: Televes



Product Description

Cascadable and QUAD-compatible multiswitch with 5 inputs (1x terrestrial and 4 polarities of a satellite) and 6 TN outputs. Can be used as a single multiswitch (star distribution) or as a cascade switch due to switchable terminating resistors. Highlights- Includes 12 V power supply unit MS-NT1208N (Ref. 732101)- Compatible with QUAD LNB due to 22KHz generator.- One switch for feeding terrestrial preamplifiers or current feed-through. A switch for feeding terrestrial preamplifiers or for power feed-through- Remote power supply via VL- DC circulation from the inputs to the top- Terrestrially active- European design, quality and manufacture Features- Very compact housing- Cast housing with best shielding properties- Colour coding of inputs and outputs- ECO mode- Very flexible: Due to switchable terminating resistors to each individual or cascade switch- 12 V power supply- Low power consumption, therefore economical operation (receiver-powered) Technical specification Number of inputs - 5 Number of cascade outputs - 5 Number of subscriber outputs - 6 Frequency range TERR.- MHz 47 ... 862 Frequency range SAT. - MHz 950 ... 2400 Input level TERR. - dB?V 92 Input level SAT. - dB?V 105 Vapour transmission TERR. - dB 2 Pass-through attenuation SAT. - dB 1.5 ... 4 Subscriber attenuation 1...8 TERR. - dB 2 Subscriber attenuation 1...8 SAT. - dB 1 Decoupling H/V - dB > 30 TN decoupling - dB > 25 Power supply - Vdc 12 Max. Current consumption (PSU) - mA 40 Max. Current consumption (STB) - mA 35 Operating temperature - °C -5 ... 45 Protection index - 20 Physical data Net weight:- 488g Gross weight:- 488g Width:- 137mm Height:- 121mm Depth:- 29mm Main product weight:- 366g

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

