

Item no.: 389268

## MSE1732K - 17 in 32 cast multi-switch EUROSWITCH, casc. without NT (MS-NT1228)

from **1.052,50 EUR**

Item no.: 389268  
shipping weight: 2.00 kg  
Manufacturer: Teledes



### Product Description

Compact multi-switch with 17 inputs (1 x terrestrial and 16 x SAT) and 32 subscriber outputs. Very low feed-through and branch attenuation due to its design. This means that the number of amplifiers required in a cascade can be reduced without compromising the signal quality, even in large installations. Use as a single switch (star topology) or as a cascade switch. In addition, TForce technology can be activated so that the terrestrial signal automatically adjusts and remains constant despite reception fluctuations. RED compliant. Highlights - Very compact design and low weight, even for models with a high number of subscribers - Very low feed-through and branch attenuation - High decoupling between inputs and outputs - Equipped with TForce technology, which automatically adjusts the terrestrial output level (TERR. AMP. ACTIVE) to the optimum level - Two power supply options: Either via a directly connected external power supply unit or, in a cascade connection, via the SAT connections - 100% European design, quality and manufacture. Features - Very good shielding values: class A. Cast housing developed and manufactured by Teledes - Very flexible: Due to switchable terminating resistors to any single or cascade switch - Low power consumption in normal operation. In addition, there is an ECO mode in which the power consumption decreases as the number of connected users decreases - 12-18V power supply range - Current circulation between all inputs and cascades - Inputs and loop-through outputs colour-coded. Technical data: Number of inputs - 17, Number of cascade outputs - 17, Number of subscriber outputs - 32, Frequency range TERR. - MHz 88 ... 862, Frequency range SAT. - MHz 950 ... 2400, Input level TERR. - dBµV 80 ... 110, Input level SAT. - dBµV 65 ... 112, Pass-through attenuation TERR. - dB < 5, Pass-through attenuation SAT. - dB 4 ... 6.5, Subscriber attenuation TERR. Active - dB 5, Subscriber attenuation TERR. Passive - dB 36, Subscriber attenuation SAT. - dB 2 ... 7, Output voltage 10Ch DVB-T - dBµV 78, Decoupling H/V - dB > 50, TN decoupling - dB > 30, Power supply - Vdc 12 ... 18, Max. Current consumption (PSU - TERR ACT.) - mA 115, Max. Current consumption (PSU - TERR PAS.) - mA 5, Max. Current consumption (STB) - mA 85, Operating temperature - °C -5 ... 45, Protection index - (IP) 20, Physical data: Net weight - 1,800g, Gross weight - 1,800g, Width - 350mm, Height - 353mm, Depth - 30mm, Main product weight - 1,800g

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

