

Item no.: 389819

MSR1942-88P - Mounting cabinet 19", 42U, 800 x 800mm, perforated doors

from **1.062,16 EUR**

Item no.: 389819
 shipping weight: 120.00 kg
 Manufacturer: Teledes



Product Description

The 42U rack cabinet is designed to house active and passive equipment that is visible from the outside and protected by a secure lockable steel structure. The cabinet is compatible with fibre optic, data cable or coaxial cable installations, allowing different technologies to be grouped in a single cabinet. Can be used for the installation of GPON headends where the infrastructure requires greater depth (up to 800 mm depth). The cabinet is equipped with depth-adjustable side profiles that allow the installation of different types of panels or devices. It has a reversible and removable front door and rear door, with flexible fixing that facilitates working in the rack. Both doors are perforated with honeycomb structure, improving passive ventilation, increasing strength while reducing the weight of the rack. The cabinet also has removable side doors with press studs that allow access to the inside of the rack via the sides - an advantage when configuring rear connections. Designed for floor mounting. Supplied with 4 screw-on feet, allowing height adjustment from 45 to 80 mm and simplifying adjustment on sloping or uneven surfaces. Supplied assembled. Dimensions (W x H x D): 800mm x 2010mm x 800mm Weight: 115kg Highlights- High load capacity and durability: made of steel with a coating based on polyester resins and lead-free pigments- Security: tempered glass, lockable front door with hinges- Laser labelling: numerical identification of each unit "HE"- Horizontal cable guides: 1U cable panels at the top and bottom of the cabinet to guide cabling from one side to the other and facilitate connections- Vertical cable guides: 10 cm of additional space on each side of the rack for easy cable routing and cable management- Convenience: two-part front door takes up less space when opening- For the installation of active equipment such as headends, a ventilation panel can be added. e.g. headends, a 120x120mm ventilation kit can be integrated Specification- Raster dimension in 19- Height mm 2010- Width mm 800- Depth mm 800- Number of height units (U) 42- Material steel- Colour black- Surface finish Electrostatic polyester powder- Number of doors 2- Rear door Yes- Material rear door steel- Max. Load capacity kg 1000- Max. Load capacity (with wheels) kg 960- Max. Max. load capacity (with feet) kg 600- Side opening Yes- Floor mounting type- L-shaped profile rail design- Earthing Yes Physical data- Net weight: 115,000 g- Gross weight: 140,000 g- Width: 800 mm- Height: 2,010 mm- Depth: 800 mm- Main product weight: 115,000 g

Specifications

Scan this QR code to
 view the product

All details, up-to-date
 prices and availability

