

Item no.: 389895

OLV-LG - Overlight - Wideband amplifier VH, low gain 13 db, with level control equaliser

from **91,96 EUR**

Item no.: 389895 shipping weight: 0.40 kg Manufacturer: Televes



Product Description

Compact wideband amplifier for overlight installations with 1 satellite. Its task is to compensate for the attenuation of the coaxial cable in the system. This amplifier can be powered via the overlight transmitter or via an external power supply. Maximum gain of up to 13 dB. It is equipped with 2 (H/V) WideBand inputs and 2 (H/V) WideBand outputs (250-2400 MHz). Use in buildings. Highlights- Independent controls for gain and equalisation- Power supply in the range from 12 V to 18 V via the jack connection or via the overlight transmitter- Particularly compact in size and weight (137x120x30mm)- 100% European design, quality and manufacture- F-connectors for HF- Die-cast housing with high shielding-Wall mounting possibleSpecification- Number of inputs 2- Number of outputs 2- Frequency band SAT- Frequency range MHz 250 ... 2400- Output voltage EN60728-3 IMD3 2tones -35dB dB?V 118- Gain dB 13- Gain adjustment dB 0 ... 13- Skew adjustment dB 0 ... 12- Decoupling dB > 25- Power supply Vdc 12 ... 18- DC throughput per SAT line mA 500-Max. Current consumption (@12V) mA 110- Max. Current consumption (@18V) mA 73- Max. Power consumption W 1.32- Protection index (IP) 20Physical data- Net weight: 381 g-Gross weight: 381 g

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

